

Package ‘criticality’

April 20, 2022

Title Modeling Fissile Material Operations in Nuclear Facilities

Version 0.9.2

Depends R (>= 3.5.0)

Description A collection of functions for modeling fissile material operations in nuclear facilities, based on Zywiec et al (2021) <[doi:10.1016/j.jress.2020.107322](https://doi.org/10.1016/j.jress.2020.107322)>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.2

Imports bnlearn, caret, dplyr, evd, fitdistrplus, ggplot2, keras, magrittr, parallel, reticulate, scales

NeedsCompilation no

Author Will Zywiec [aut, cre] (<<https://orcid.org/0000-0002-1842-9599>>)

Maintainer Will Zywiec <willzywiec@gmail.com>

Repository CRAN

Date/Publication 2022-04-20 17:52:29 UTC

R topics documented:

BN	2
Model	3
NN	3
Plot	5
Risk	6
Sample	7
Scale	8
Tabulate	9
Test	10
Index	11

BN	<i>BN Function</i>
----	--------------------

Description

This function creates a Bayesian network from pre-formatted nuclear facility data.

Usage

```
BN(dist = "gamma", facility.data, ext.dir)
```

Arguments

<code>dist</code>	Truncated probability distribution (e.g., "gamma", "normal")
<code>facility.data</code>	.csv file name
<code>ext.dir</code>	External directory (full path)

Value

A Bayesian network that models fissile material operations (op), controls (ctrl), and parameters that affect nuclear criticality safety

Examples

```
ext.dir <- paste0(tempdir(), "/criticality/extdata")
dir.create(ext.dir, recursive = TRUE, showWarnings = FALSE)

extdata <- paste0(.libPaths()[1], "/criticality/extdata")
file.copy(paste0(extdata, "/facility.csv"), ext.dir, recursive = TRUE)
file.copy(paste0(extdata, "/mcnp-dataset.RData"), ext.dir, recursive = TRUE)

BN(
  dist = "gamma",
  facility.data = "facility.csv",
  ext.dir = ext.dir
)
```

Model	<i>Model Function</i>
-------	-----------------------

Description

This function builds the deep neural network metamodel architecture.

Usage

```
Model(
  dataset,
  layers = "8192-256-256-256-256-16",
  loss = "sse",
  opt.alg = "adamax",
  learning.rate = 0.00075,
  ext.dir
)
```

Arguments

dataset	Training and test data
layers	String that defines the deep neural network architecture (e.g., "64-64")
loss	Loss function
opt.alg	Optimization algorithm
learning.rate	Learning rate
ext.dir	External directory (full path)

Value

A deep neural network metamodel of Monte Carlo radiation transport code simulation data

NN	<i>NN Function</i>
----	--------------------

Description

This function imports the Tabulate, Scale, Model, Fit, Plot, and Test functions to train an ensemble of deep neural networks to predict keff values.

Usage

```

NN(
  batch.size = 8192,
  code = "mcnp",
  dataset,
  ensemble.size = 5,
  epochs = 1500,
  layers = "8192-256-256-256-256-16",
  loss = "sse",
  opt.alg = "adamax",
  learning.rate = 0.00075,
  val.split = 0.2,
  overwrite = FALSE,
  replot = TRUE,
  verbose = FALSE,
  ext.dir,
  training.dir = NULL
)

```

Arguments

<code>batch.size</code>	Batch size
<code>code</code>	Monte Carlo radiation transport code (e.g., "cog", "mcnp")
<code>dataset</code>	Training and test data
<code>ensemble.size</code>	Number of deep neural networks in the ensemble
<code>epochs</code>	Number of training epochs
<code>layers</code>	String that defines the deep neural network architecture (e.g., "64-64")
<code>loss</code>	Loss function
<code>opt.alg</code>	Optimization algorithm
<code>learning.rate</code>	Learning rate
<code>val.split</code>	Validation split
<code>overwrite</code>	Boolean (TRUE/FALSE) that determines if files should be overwritten
<code>replot</code>	Boolean (TRUE/FALSE) that determines if .png files should be replotted
<code>verbose</code>	Boolean (TRUE/FALSE) that determines if TensorFlow and Test function output should be displayed
<code>ext.dir</code>	External directory (full path)
<code>training.dir</code>	Training directory (full path)

Value

A list of lists containing an ensemble of deep neural networks and weights

Examples

```
ext.dir <- paste0(tempdir(), "/criticality/extdata")
dir.create(ext.dir, recursive = TRUE, showWarnings = FALSE)

extdata <- paste0(.libPaths()[1], "/criticality/extdata")
file.copy(paste0(extdata, "/facility.csv"), ext.dir, recursive = TRUE)
file.copy(paste0(extdata, "/mcnp-dataset.RData"), ext.dir, recursive = TRUE)

config <- FALSE
try(config <- reticulate::py_config()$available)
try(if (config == TRUE) {
  NN(
    batch.size = 128,
    code = "mcnp",
    ensemble.size = 1,
    epochs = 10,
    layers = "256-256-16",
    loss = "sse",
    opt.alg = "adamax",
    learning.rate = 0.00075,
    val.split = 0.2,
    replot = FALSE,
    verbose = FALSE,
    ext.dir = ext.dir
  )
})
```

Plot

Plot Function

Description

This function generates and saves plots and data.

Usage

```
Plot(i, history = NULL, plot.dir)
```

Arguments

<code>i</code>	Model number
<code>history</code>	Training history
<code>plot.dir</code>	Plot directory (full path)

Value

No output (generates and saves ggplot2 files and training histories)

 Risk

Risk Function

Description

This function imports the Sample function and estimates process criticality accident risk.

Usage

```
Risk(
  bn,
  code = "mcnp",
  cores = parallel::detectCores()/2,
  dist = "gamma",
  facility.data,
  keff.cutoff = 0.9,
  metamodel,
  risk.pool = 100,
  sample.size = 1e+09,
  usl = 0.95,
  ext.dir
)
```

Arguments

bn	Bayesian network
code	Monte Carlo radiation transport code (e.g., "cog", "mcnp")
cores	Number of CPU cores to use for generating Bayesian network samples
dist	Truncated probability distribution (e.g., "gamma", "normal")
facility.data	.csv file name
keff.cutoff	keff cutoff value (e.g., keff >= 0.9)
metamodel	List of deep neural network metamodels and weights
risk.pool	Number of times risk is calculated
sample.size	Number of samples used to calculate risk
usl	Upper subcritical limit (e.g., keff >= 0.95)
ext.dir	External directory (full path)

Value

A list of lists containing process criticality accident risk estimates and Bayesian network samples

Examples

```

ext.dir <- paste0(tempdir(), "/criticality/extdata")
dir.create(ext.dir, recursive = TRUE, showWarnings = FALSE)

extdata <- paste0(.libPaths()[1], "/criticality/extdata")
file.copy(paste0(extdata, "/facility.csv"), ext.dir, recursive = TRUE)
file.copy(paste0(extdata, "/mcnp-dataset.RData"), ext.dir, recursive = TRUE)

config <- FALSE
try(config <- reticulate::py_config()$available)
try(if (config == TRUE) {
  Risk(
    bn = BN(
      facility.data = "facility.csv",
      dist = "gamma",
      ext.dir = ext.dir),
    code = "mcnp",
    cores = 1,
    dist = "gamma",
    facility.data = "facility.csv",
    keff.cutoff = 0.5,
    metamodel = NN(
      batch.size = 128,
      code = "mcnp",
      ensemble.size = 1,
      epochs = 10,
      layers = "8192-256-256-256-16",
      loss = "sse",
      opt.alg = "adamax",
      learning.rate = 0.00075,
      val.split = 0.2,
      replot = TRUE,
      verbose = TRUE,
      ext.dir = ext.dir),
    risk.pool = 10,
    sample.size = 1e+04,
    usl = 0.95,
    ext.dir = ext.dir
  )
})

```

Sample

Sample Function

Description

This function samples the Bayesian network and generates keff predictions using a deep neural network metamodel.

Usage

```

Sample(
  bn,
  code = "mcnp",
  cores = parallel::detectCores()/2,
  keff.cutoff = 0.9,
  metamodel,
  sample.size = 1e+09,
  ext.dir,
  risk.dir = NULL
)

```

Arguments

<code>bn</code>	Bayesian network object
<code>code</code>	Monte Carlo radiation transport code (e.g., "cog", "mcnp")
<code>cores</code>	Number of CPU cores to use for generating Bayesian network samples
<code>keff.cutoff</code>	keff cutoff value (e.g., 0.9)
<code>metamodel</code>	List of deep neural network metamodels and weights
<code>sample.size</code>	Number of samples used to calculate risk
<code>ext.dir</code>	External directory (full path)
<code>risk.dir</code>	Risk directory

Value

A list of Bayesian network samples with predicted keff values

Scale	<i>Scale Function</i>
-------	-----------------------

Description

This function centers, scales, and one-hot encodes variables.

Usage

```
Scale(code = "mcnp", dataset = NULL, output, ext.dir)
```

Arguments

<code>code</code>	Monte Carlo radiation transport code (e.g., "cog", "mcnp")
<code>dataset</code>	Training and test data
<code>output</code>	Processed output from Monte Carlo radiation transport code simulations
<code>ext.dir</code>	External directory (full path)

Value

A list of centered, scaled, and one-hot-encoded training and test data

Tabulate

Tabulate Function

Description

This function imports the Scale function and loads/saves training and test data.

Usage

```
Tabulate(code = "mcnp", ext.dir)
```

Arguments

code	Monte Carlo radiation transport code (e.g., "cog", "mcnp")
ext.dir	External directory (full path)

Value

A list of centered, scaled, and one-hot-encoded training and test data

Examples

```
ext.dir <- paste0(tempdir(), "/criticality/extdata")
dir.create(ext.dir, recursive = TRUE, showWarnings = FALSE)

extdata <- paste0(.libPaths()[1], "/criticality/extdata")
file.copy(paste0(extdata, "/facility.csv"), ext.dir, recursive = TRUE)
file.copy(paste0(extdata, "/mcnp-dataset.RData"), ext.dir, recursive = TRUE)

Tabulate(
  code = "mcnp",
  ext.dir = ext.dir
)
```

Test	<i>Test Function</i>
------	----------------------

Description

This function calculates deep neural network metamodel weights and generates keff predictions for all training and test data.

Usage

```
Test(  
  dataset,  
  ensemble.size = 5,  
  loss = "sse",  
  verbose = FALSE,  
  ext.dir,  
  training.dir  
)
```

Arguments

dataset	Training and test data
ensemble.size	Number of deep neural networks in the ensemble
loss	Loss function
verbose	Boolean (TRUE/FALSE) that determines if Test function output should be displayed
ext.dir	External directory (full path)
training.dir	Training directory (full path)

Value

A list of deep neural network weights

Index

BN, [2](#)

Model, [3](#)

NN, [3](#)

Plot, [5](#)

Risk, [6](#)

Sample, [7](#)

Scale, [8](#)

Tabulate, [9](#)

Test, [10](#)