

Package ‘iheiddown’

November 17, 2021

Title For Writing Graduate Institute Geneva Documents

Description A set of tools to support writing various documents according to the Graduate Institute of International and Development Studies conventions and regulations.

The most common use will be for writing and compiling theses or thesis chapters, as drafts or for examination with all the correct preamble content. However, the package also offers the creation of html presentation slides via 'xaringan', the capacity to write problem sets and, for course instructors, the ability to create syllabi.

The package includes additional functions for institutional color palettes and an institutional 'ggplot' theme, as well as a function for word counts and a bibliographical analysis toolkit.

Date 2021-11-16

Version 0.8.6

URL <https://github.com/jhollway/iheiddown>

BugReports <https://github.com/jhollway/iheiddown/issues>

Depends R (>= 3.5.0)

License MIT + file LICENSE

Imports bookdown, dplyr, ggplot2, rmarkdown, xaringan, crayon, pdftools, rlang, servr, readr, rstudioapi, tibble, tidytext, bib2df, purrr, stringr, fs, usethis, gender, remotes

Encoding UTF-8

RoxygenNote 7.1.2

Suggests testthat, kableExtra, knitr, DT, leaflet

VignetteBuilder knitr

NeedsCompilation no

Author James Hollway [aut, cre, cph] (<<https://orcid.org/0000-0002-8361-9647>>), Bernhard Bieri [ctb] (<<https://orcid.org/0000-0001-5943-9059>>)

Maintainer James Hollway <james.hollway@graduateinstitute.ch>

Repository CRAN

Date/Publication 2021-11-17 11:40:06 UTC

R topics documented:

advdate	2
bookdown_profile	3
chapter_pdf	3
countwords	4
fix_bib	4
iheid_palette	5
iheid_palettes	6
preview	6
problemset_pdf	7
syllabus_pdf	8
theme_iheid	8
thesis_pdf	10
Index	12

advdate	<i>Advance dates by week</i>
---------	------------------------------

Description

This function takes a start date, e.g. of a course, and advances it by a number of weeks. This function is used in the syllabus template.

Usage

```
advdate(startdate, week)
```

Arguments

startdate	The first date in the series (e.g. first day of class).
week	The number of weeks into the series. Week 1 is the first date in the series.

Value

A vector of dates in the format "dd mmm" in parentheses.

Examples

```
advdate("2021-06-23", 1:3)
```

bookdown_profile	<i>Manage iheiddown profile</i>
------------------	---------------------------------

Description

This RStudio Addin opens up the `~/_bookdown.yml` file for users to edit. If the file doesn't exist, it will create one.

Usage

```
bookdown_profile()
```

Value

Opens or creates a bookdown profile YAML file for the current thesis.

chapter_pdf	<i>Creates an R Markdown PDF Thesis chapter</i>
-------------	---

Description

This function can be used in the header of each constituent chapter of an IHEID thesis to output a draft version of the chapter for proofreading or sending to your supervisor.

Usage

```
chapter_pdf(input, ...)
```

Arguments

<code>input</code>	Rmd input file that will be processed by the function.
<code>...</code>	Instructions passed to the function from a correctly specified .Rmd document

Value

A modified pdf_document based on the IHEID Thesis LaTeX template

Examples

```
## Not run:  
knit: iheiddown::chapter_pdf  
  
## End(Not run)
```

`countwords`*A function for counting words in an Rmarkdown document.*

Description

This function takes a path to a .Rmd file and returns a word count. For best results each sentence should start on a new line. Inline code chunks should also start on a new line.

Usage`count_words(file)``count_words2(file)`**Arguments**`file` A path to a .Rmd file**Value**

A scalar representing the number of words in the document.

Examples

```
rmarkdown::draft(file = "test", template = "html_vignette",
package = "rmarkdown", create_dir = TRUE, edit = FALSE)
iheiddown::count_words("test/test.Rmd")
unlink("test", recursive = TRUE)
```

`fix_bib`*Reporting bibliographic statistics*

Description

These functions are useful for calculating salient statistics on the bibliographies used for dissertations or syllabi. They include the following functions/metrics:

Usage`fix_bib(bib_file)``percent_female(bib_file, rmd_file, by = c("author", "publication"))``mean_year(bib_file, rmd_file)`

```
mean_pages(bib_file, rmd_file)
```

```
total_pages(bib_file, rmd_file)
```

Arguments

bib_file A .bib file for the project. If not given, the functions will search for a .bib file in the folder associated with the file the source editor has open.

rmd_file A .rmd file. If not given, the functions will check to see whether the current file open in the source editor is an .rmd file, and if so use that.

by A string in c("author", "publication") which determines if the percentage of female authors is computed across all papers or the percentage represents the proportion of papers written by at least one woman.

Details

`percent_female()` Displays the percentage of authors in a .bib file that are female. See the {gender} package for more details.

`mean_year()` Displays the average year of publication of the items in a given .bib file.

`mean_pages()` Displays the average number of pages of the items in a given .bib file.

`total_pages()` Displays the total number of pages of all items in a given .bib file.

Value

Prints a summary statistic (e.g. mean or proportion)

iheid_palette *An IHEID palette generator*

Description

These are a few color palettes useful for members of the Graduate Institute. This function calls one of three official palettes in [iheid_palette](#): for the Institute, for the Centres, and for the SDGs.

Usage

```
iheid_palette(name, n, type = c("discrete", "continuous"))
```

Arguments

name Name of desired palette. Current choices are: IHEID, Centres, and SDGs.

n Number of colors desired. If omitted, uses all colours.

type Either "continuous" or "discrete". Use continuous if you want to automatically interpolate between colours.

Value

A vector of colours.

Source

Adapted from <https://github.com/karthik/wesanderson/blob/master/R/colors.R>

Examples

```
iheid_palette("IHEID")
iheid_palette("Centres")
iheid_palette("SDGs")

# If you need more colours than normally found in a palette, you
# can use a continuous palette to interpolate between existing
# colours
pal <- iheid_palette(21, name = "Centres", type = "continuous")
image(volcano, col = pal)
```

iheid_palettes	<i>Complete list of palettes</i>
----------------	----------------------------------

Description

Use `iheid_palette` to construct palettes of desired length.

Usage

```
iheid_palettes
```

Format

An object of class `list` of length 3.

preview	<i>Previewing rmarkdown documents</i>
---------	---------------------------------------

Description

Use the `servr` package to continuously serve and reload the Rmd document. Run `preview_start()` function while viewing the Rmd panel of your presentation. To stop the server, run `preview_stop()`.

Usage

```
preview_start(file_path, ...)

preview_stop(which = NULL)
```

Arguments

file_path	The input Rmd file path (if missing and in RStudio, the current active document is used).
...	Additional arguments passed to <code>rmarkdown::render()</code> .
which	An integer vector of the server IDs; by default, IDs of all existing servers in the current R session obtained from <code>daemon_list()</code> , i.e., all daemon servers will be stopped by default.

Value

Starts serving the current files to RStudio's Viewer pane.

Stops serving the current files to RStudio's Viewer pane.

References

xaringan

problemset_pdf	<i>Creates an R Markdown PDF Problem Set document</i>
----------------	---

Description

This is a function called in output in the YAML of the driver Rmd file to specify using the IHEID Problem Set LaTeX template file.

Usage

```
problemset_pdf(input, ...)
```

Arguments

input	The name of the .Rmd file to serve as input.
...	Instructions passed to the function from a correctly specified .Rmd document

Value

A modified pdf_document based on the IHEID Problem Set LaTeX template, automatically named by course and date.

Examples

```
## Not run:
output:
  iheiddown::problemset_pdf:
    input: "Untitled.Rmd"
    # Replace with whatever the name of this file is, e.g. "MINT001.Rmd"

## End(Not run)
```

syllabus_pdf	<i>Creates an R Markdown PDF Syllabus document</i>
--------------	--

Description

This is a function called in output in the YAML of the driver Rmd file to specify using the IHEID Syllabus LaTeX template file.

Usage

```
syllabus_pdf(input, ...)
```

Arguments

input	The name of the .Rmd file to serve as input.
...	Instructions passed to the function from a correctly specified .Rmd document

Value

A modified pdf_document based on the IHEID Syllabus LaTeX template, automatically named by course and date.

Examples

```
## Not run:
output:
  iheiddown::syllabus_pdf:
    input: "Untitled.Rmd"
    # Replace with whatever the name of this file is, e.g. "MINT001.Rmd"

## End(Not run)
```

theme_iheid	<i>A ggplot2 theme for IHEID style plots. Adapted from Hrbrmstr's ipsum theme.</i>
-------------	--

Description

A ggplot2 theme for IHEID style plots. Adapted from Hrbrmstr's ipsum theme.

Usage

```
theme_iheid(  
  base_family = "sans",  
  base_size = 11.5,  
  plot_title_family = base_family,  
  plot_title_size = 18,  
  plot_title_face = "bold",  
  plot_title_margin = 10,  
  subtitle_family = base_family,  
  subtitle_size = 12,  
  subtitle_face = "plain",  
  subtitle_margin = 15,  
  strip_text_family = base_family,  
  strip_text_size = 12,  
  strip_text_face = "plain",  
  caption_family = base_family,  
  caption_size = 9,  
  caption_face = "italic",  
  caption_margin = 10,  
  axis_text_size = base_size,  
  axis_title_family = subtitle_family,  
  axis_title_size = 9,  
  axis_title_face = "plain",  
  axis_title_just = "rt",  
  plot_margin = margin(30, 30, 30, 30),  
  grid_col = "grey85",  
  grid = TRUE,  
  axis_col = iheid_palette("IHEID")["IHEIDBlack"],  
  axis = FALSE,  
  ticks = FALSE  
)
```

Arguments

`base_family`, `base_size`
base font family and size

`plot_title_family`, `plot_title_face`, `plot_title_size`, `plot_title_margin`
plot title family, face, size and margin

`subtitle_family`, `subtitle_face`, `subtitle_size`
plot subtitle family, face and size

`subtitle_margin`
plot subtitle margin bottom (single numeric value)

`strip_text_family`, `strip_text_face`, `strip_text_size`
facet label font family, face and size

`caption_family`, `caption_face`, `caption_size`, `caption_margin`
plot caption family, face, size and margin

`axis_text_size` font size of axis text

`axis_title_family`, `axis_title_face`, `axis_title_size`
 axis title font family, face and size
`axis_title_just`
 axis title font justification, one of [blmcr]

`plot_margin` plot margin (specify with `ggplot2::margin()`)
`grid_col`, `axis_col`
 grid & axis colors; both default to #cccccc

`grid` panel grid (TRUE, FALSE, or a combination of X, x, Y, y)
`axis` add x or y axes? TRUE, FALSE, "xy"
`ticks` ticks if TRUE add ticks

Value

Themes the current ggplot to current IHEID guidelines.

Examples

```

library(ggplot2)
library(dplyr)

# seminal scatterplot
ggplot(mtcars, aes(mpg, wt)) +
  geom_point() +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 scatterplot example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_iheid()

# seminal bar chart
count(mpg, class) %>%
  ggplot(aes(class, n)) +
  geom_col() +
  geom_text(aes(label=n), nudge_y=3) +
  labs(x="Fuel efficiency (mpg)", y="Weight (tons)",
       title="Seminal ggplot2 bar chart example",
       subtitle="A plot that is only useful for demonstration purposes",
       caption="Brought to you by the letter 'g'") +
  theme_iheid(grid="Y") +
  theme(axis.text.y=element_blank())

```

Description

This is a function called in output in the YAML of the driver Rmd file to specify using the IHEID Thesis LaTeX template file.

Usage

```
thesis_pdf(input = ".", ...)
```

Arguments

<code>input</code>	Rmd input file that will be processed by the function.
<code>...</code>	Instructions passed to the function from a correctly specified .Rmd document

Value

A modified pdf_document based on the IHEID Thesis LaTeX template

Examples

```
## Not run:  
knit: iheiddown::thesis_pdf  
  
## End(Not run)
```

Index

- * **colors**

- iheid_palette, 5

- * **datasets**

- iheid_palettes, 6

advdate, 2

bibstats (fix_bib), 4

bookdown_profile, 3

chapter_pdf, 3

count_words (countwords), 4

count_words2 (countwords), 4

countwords, 4

fix_bib, 4

iheid_palette, 5, 5, 6

iheid_palettes, 6

mean_pages (fix_bib), 4

mean_year (fix_bib), 4

percent_female (fix_bib), 4

preview, 6

preview_start (preview), 6

preview_stop (preview), 6

problemset_pdf, 7

render, 7

syllabus_pdf, 8

theme_iheid, 8

thesis_pdf, 10

total_pages (fix_bib), 4