

Package ‘noctua’

January 17, 2022

Type Package

Title Connect to 'AWS Athena' using R 'AWS SDK' 'paws' ('DBI' Interface)

Version 2.5.0

Description Designed to be compatible with the 'R' package 'DBI' (Database Interface) when connecting to Amazon Web Service ('AWS') Athena <<https://aws.amazon.com/athena/>>.

To do this the 'R' 'AWS' Software Development Kit ('SDK') 'paws' <<https://github.com/paws-r/paws>> is used as a driver.

Imports data.table (>= 1.12.4), DBI (>= 0.7), methods, paws (>= 0.1.5), stats, utils, uuid (>= 0.1-4)

Suggests arrow, bit64, dplyr (>= 0.8.0), dbplyr (>= 1.4.3), readr, testthat, tibble, vroom (>= 1.2.0), covr, knitr, rmarkdown, jsonify, jsonlite

VignetteBuilder knitr

Depends R (>= 3.2.0)

License MIT + file LICENSE

Encoding UTF-8

RoxxygenNote 7.1.2

URL <https://github.com/DyfanJones/noctua>

BugReports <https://github.com/DyfanJones/noctua/issues>

Collate 'utils.R' 'dplyr_integration.R' 'noctua.R' 'Driver.R'
'Connection.R' 'DataTypes.R' 'File_Parser.R' 'Options.R'
'fetch_utils.R' 'Result.R' 'Table.R' 'View.R'
'athena_low_api.R' 'column_parser.R' 'sql_translate_utils.R'
'sql_translate_env.R' 'zzz.R'

NeedsCompilation no

Author Dyfan Jones [aut, cre]

Maintainer Dyfan Jones <dyfan.r.jones@gmail.com>

Repository CRAN

Date/Publication 2022-01-17 17:02:46 UTC

R topics documented:

noctua-package	3
assume_role	3
athena	5
AthenaWriteTables	5
backend_dbplyr_v1	9
backend_dbplyr_v2	9
dbClearResult	10
dbColumnInfo	11
dbConnect,AthenaDriver-method	12
dbConvertTable	15
dbDataType,AthenaDriver,ANY-method	17
dbDisconnect	18
dbExistsTable	19
dbFetch	20
dbGetInfo	21
dbGetPartition	22
dbGetQuery	24
dbGetStatement	25
dbGetTables	26
dbHasCompleted	27
dbIsValid	28
dbListFields	29
dbListTables	30
dbplyr_edition	31
dbQuote	32
dbRemoveTable	32
dbShow	34
dbStatistics	35
db_compute	36
db_connection_describe	37
db_copy_to	38
db_desc	40
noctua_options	41
Query	42
session_token	43
sqlCreateTable	45
sqlData	47
sql_translate_env	48
work_group	48

noctua-package

noctua: a DBI interface into Athena using paws SDK

Description

noctua provides a seamless DBI interface into Athena using the R package [paws](#).

Goal of Package

The goal of the noctua package is to provide a DBI-compliant interface to [Amazon's Athena](#) using paws software development kit (SDK). This allows for an efficient, easy setup connection to Athena using the paws SDK as a driver.

AWS Command Line Interface

As noctua is using paws as it's backend, [AWS Command Line Interface \(AWS CLI\)](#) can be used to remove user credentials when interacting with Athena.

This allows AWS profile names to be set up so that noctua can connect to different accounts from the same machine, without needing hard code any credentials.

Author(s)

Maintainer: Dyfan Jones <dyfan.r.jones@gmail.com>

See Also

Useful links:

- <https://github.com/DyfanJones/noctua>
 - Report bugs at <https://github.com/DyfanJones/noctua/issues>
-

assume_role

Assume AWS ARN Role

Description

Returns a set of temporary security credentials that you can use to access AWS resources that you might not normally have access to ([link](#)). These temporary credentials consist of an access key ID, a secret access key, and a security token. Typically, you use AssumeRole within your account or for cross-account access.

Usage

```
assume_role(
  profile_name = NULL,
  region_name = NULL,
  role_arn = NULL,
  role_session_name = sprintf("noctua-session-%s", as.integer(Sys.time())),
  duration_seconds = 3600L,
  set_env = FALSE
)
```

Arguments

profile_name	The name of a profile to use. If not given, then the default profile is used. To set profile name, the AWS Command Line Interface (AWS CLI) will need to be configured. To configure AWS CLI please refer to: Configuring the AWS CLI .
region_name	Default region when creating new connections. Please refer to link for AWS region codes (region code example: Region = EU (Ireland) region_name = "eu-west-1")
role_arn	The Amazon Resource Name (ARN) of the role to assume (such as arn:aws:sts::123456789012:assum
role_session_name	An identifier for the assumed role session. By default 'noctua' creates a session name sprintf("noctua-session-%s",as.integer(Sys.time()))
duration_seconds	The duration, in seconds, of the role session. The value can range from 900 seconds (15 minutes) up to the maximum session duration setting for the role. This setting can have a value from 1 hour to 12 hours. By default duration is set to 3600 seconds (1 hour).
set_env	If set to TRUE environmental variables AWS_ACCESS_KEY_ID, AWS_SECRET_ACCESS_KEY and AWS_SESSION_TOKEN will be set.

Value

assume_role() returns a list containing: "AccessKeyId", "SecretAccessKey", "SessionToken" and "Expiration"

See Also

[dbConnect](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.

library(noctua)
library(DBI)
```

```
# Assuming demo ARN role
assume_role(profile_name = "YOUR_PROFILE_NAME",
            role_arn = "arn:aws:sts::123456789012:assumed-role/role_name/role_session_name",
            set_env = TRUE)

# Connect to Athena using ARN Role
con <- dbConnect(noctua::athena())

## End(Not run)
```

athena

Athena Driver

Description

Driver for an Athena paws connection.

Usage

athena()

Value

athena() returns a s4 class. This class is used active Athena method for [dbConnect](#)

See Also

[dbConnect](#)

AthenaWriteTables

Convenience functions for reading/writing DBMS tables

Description

Convenience functions for reading/writing DBMS tables

Usage

```
## S4 method for signature 'AthenaConnection,character,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  row.names = NA,
  field.types = NULL,
```

```

partition = NULL,
s3.location = NULL,
file.type = c("tsv", "csv", "parquet", "json"),
compress = FALSE,
max.batch = Inf,
...
)

## S4 method for signature 'AthenaConnection,Id,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  row.names = NA,
  field.types = NULL,
  partition = NULL,
  s3.location = NULL,
  file.type = c("tsv", "csv", "parquet", "json"),
  compress = FALSE,
  max.batch = Inf,
  ...
)

## S4 method for signature 'AthenaConnection,SQL,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  row.names = NA,
  field.types = NULL,
  partition = NULL,
  s3.location = NULL,
  file.type = c("tsv", "csv", "parquet", "json"),
  compress = FALSE,
  max.batch = Inf,
  ...
)

```

Arguments

conn	An AthenaConnection object, produced by [DBI::dbConnect()]
name	A character string specifying a table name. Names will be automatically quoted so you can use any sequence of characters, not just any valid bare table name.
value	A data.frame to write to the database.

overwrite	Allows overwriting the destination table. Cannot be TRUE if append is also TRUE.
append	Allow appending to the destination table. Cannot be TRUE if overwrite is also TRUE. Existing Athena DDL file type will be retained and used when uploading data to AWS Athena. If parameter file.type doesn't match AWS Athena DDL file type a warning message will be created notifying user and noctua will use the file type for the Athena DDL. When appending to an Athena DDL that has been created outside of noctua. noctua can support the following SerDes and Data Formats. <ul style="list-style-type: none"> • csv/tsv: LazySimpleSerDe • parquet: Parquet SerDe • json: JSON SerDe Libraries
row.names	Either TRUE, FALSE, NA or a string. If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector. A string is equivalent to TRUE, but allows you to override the default name. For backward compatibility, NULL is equivalent to FALSE.
field.types	Additional field types used to override derived types.
partition	Partition Athena table (needs to be a named list or vector) for example: c(var1 = "2019-20-13")
s3.location	s3 bucket to store Athena table, must be set as a s3 uri for example ("s3://mybucket/data/"). By default, the s3.location is set to s3 staging directory from AthenaConnection object. Note: When creating a table for the first time s3.location will be formatted from "s3://mybucket/data/" to the following syntax "s3://{{mybucket}/data}/{schema}/{table}" this is to support tables with the same name but existing in different schemas. If schema isn't specified in name parameter then the schema from dbConnect is used instead.
file.type	What file type to store data.frame on s3, noctua currently supports ["tsv", "csv", "parquet", "json"]. Default delimited file type is "tsv", in previous versions of noctua (<= 1.4.0) file type "csv" was used as default. The reason for the change is that columns containing Array/JSON format cannot be written to Athena due to the separating value ",". This would cause issues with AWS Athena. Note: "parquet" format is supported by the arrow package and it will need to be installed to utilise the "parquet" format. "json" format is supported by jsonlite package and it will need to be installed to utilise the "json" format.
compress	FALSE TRUE To determine if to compress file.type. If file type is ["csv", "tsv"] then "gzip" compression is used, for file type "parquet" "snappy" compression is used. Currently noctua doesn't support compression for "json" file type.
max.batch	Split the data frame by max number of rows i.e. 100,000 so that multiple files can be uploaded into AWS S3. By default when compression is set to TRUE and file.type is "csv" or "tsv" max.batch will split data.frame into 20 batches. This is to help the performance of AWS Athena when working with files compressed in "gzip" format. max.batch will not split the data.frame when loading file in parquet format. For more information please go to link
...	Other arguments used by individual methods.

Value

`dbWriteTable()` returns TRUE, invisibly. If the table exists, and both append and overwrite arguments are unset, or append = TRUE and the data frame with the new data has different column names, an error is raised; the remote table remains unchanged.

See Also

[dbWriteTable](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# List existing tables in Athena
dbListTables(con)

# Write data.frame to Athena table
dbWriteTable(con, "mtcars", mtcars,
            partition=c("TIMESTAMP" = format(Sys.Date(), "%Y%m%d")),
            s3.location = "s3://mybucket/data/")

# Read entire table from Athena
dbReadTable(con, "mtcars")

# List all tables in Athena after uploading new table to Athena
dbListTables(con)

# Checking if uploaded table exists in Athena
dbExistsTable(con, "mtcars")

# using default s3.location
dbWriteTable(con, "iris", iris)

# Read entire table from Athena
dbReadTable(con, "iris")

# List all tables in Athena after uploading new table to Athena
dbListTables(con)

# Checking if uploaded table exists in Athena
dbExistsTable(con, "iris")

# Disconnect from Athena
dbDisconnect(con)
```

```
## End(Not run)
```

backend_dbplyr_v1 *Athena S3 implementation of dbplyr backend functions (api version 1).*

Description

These functions are used to build the different types of SQL queries. The AWS Athena implementation give extra parameters to allow access the to standard DBI Athena methods. They also utilise AWS Glue to speed up sql query execution.

Usage

```
db_explain.AthenaConnection(con, sql, ...)
db_query_fields.AthenaConnection(con, sql, ...)
```

Arguments

con	A dbConnect object, as returned by dbConnect()
sql	SQL code to be sent to AWS Athena
...	other parameters, currently not implemented

Value

db_explain Returns [AWS Athena explain statement](#)
db_query_fields Returns sql query column names

backend_dbplyr_v2 *Athena S3 implementation of dbplyr backend functions (api version 2).*

Description

These functions are used to build the different types of SQL queries. The AWS Athena implementation give extra parameters to allow access the to standard DBI Athena methods. They also utilise AWS Glue to speed up sql query execution.

Usage

```
sql_query_explain.AthenaConnection(con, sql, format = "text", type = NULL, ...)
sql_query_fields.AthenaConnection(con, sql, ...)
sql_escape_date.AthenaConnection(con, x)
sql_escape_datetime.AthenaConnection(con, x)
```

Arguments

con	A dbConnect object, as returned by dbConnect()
sql	SQL code to be sent to AWS Athena
format	returning format for explain queries, default set to "text". Other formats can be found: https://docs.aws.amazon.com/athena/latest/ug/athena-explain-statement.html
type	return plan for explain queries, default set to 'NULL'. Other type can be found: https://docs.aws.amazon.com/athena/latest/ug/athena-explain-statement.html
...	other parameters, currently not implemented
x	R object to be transformed into athena equivalent

Value

sql_query_explain Returns sql query for [AWS Athena explain statement](#)
sql_query_fields Returns sql query column names
sql_escape_date Returns sql escaping from dates
sql_escape_datetime Returns sql escaping from date times

dbClearResult

*Clear Results***Description**

Frees all resources (local and Athena) associated with result set. It does this by removing query output in AWS S3 Bucket, stopping query execution if still running and removed the connection resource locally.

Usage

```
## S4 method for signature 'AthenaResult'
dbClearResult(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

dbClearResult() returns TRUE, invisibly.

Note

If a user does not have permission to remove AWS S3 resource from AWS Athena output location, then an AWS warning will be returned. It is better use query caching [noctua_options](#) so that the warning doesn't repeatedly show.

See Also[dbIsValid](#)**Examples**

```
## Not run:  
# Note:  
# - Require AWS Account to run below example.  
# - Different connection methods can be used please see `noctua::dbConnect` documentation  
  
library(DBI)  
  
# Demo connection to Athena using profile name  
con <- dbConnect(noctua::athena())  
  
res <- dbSendQuery(con, "show databases")  
dbClearResult(res)  
  
# Check if connection is valid after closing connection  
dbDisconnect(con)  
  
## End(Not run)
```

[dbColumnInfo](#)*Information about result types*

Description

Produces a data.frame that describes the output of a query.

Usage

```
## S4 method for signature 'AthenaResult'  
dbColumnInfo(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbColumnInfo()` returns a data.frame with as many rows as there are output fields in the result. The data.frame has two columns (field_name, type).

See Also

[dbHasCompleted](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `RAthena::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Get Column information from query
res <- dbSendQuery(con, "select * from information_schema.tables")
dbColumnInfo(res)
dbClearResult(res)

# Disconnect from Athena
dbDisconnect(con)

## End(Not run)
```

dbConnect,AthenaDriver-method

Connect to Athena using R's sdk paws

Description

It is never advised to hard-code credentials when making a connection to Athena (even though the option is there). Instead it is advised to use `profile_name` (set up by [AWS Command Line Interface](#)), [Amazon Resource Name roles](#) or environmental variables. Here is a list of supported environment variables:

- **AWS_ACCESS_KEY_ID:** is equivalent to the `dbConnect` parameter - `aws_access_key_id`
- **AWS_SECRET_ACCESS_KEY:** is equivalent to the `dbConnect` parameter - `aws_secret_access_key`
- **AWS_SESSION_TOKEN:** is equivalent to the `dbConnect` parameter - `aws_session_token`
- **AWS_ROLE_ARN:** is equivalent to the `dbConnect` parameter - `role_arn`
- **AWS_EXPIRATION:** is equivalent to the `dbConnect` parameter - `duration_seconds`
- **AWS_ATHENA_S3_STAGING_DIR:** is equivalent to the `dbConnect` parameter - `s3_staging_dir`

- **AWS_ATHENA_WORK_GROUP:** is equivalent to dbConnect parameter - work_group
- **AWS_REGION:** is equivalent to dbConnect parameter - region_name

NOTE: If you have set any environmental variables in .Renviron please restart your R in order for the changes to take affect.

Usage

```
## S4 method for signature 'AthenaDriver'
dbConnect(
  drv,
  aws_access_key_id = NULL,
  aws_secret_access_key = NULL,
  aws_session_token = NULL,
  schema_name = "default",
  work_group = NULL,
  poll_interval = NULL,
  encryption_option = c("NULL", "SSE_S3", "SSE_KMS", "CSE_KMS"),
  kms_key = NULL,
  profile_name = NULL,
  role_arn = NULL,
  role_session_name = sprintf("noctua-session-%s", as.integer(Sys.time())),
  duration_seconds = 3600L,
  s3_staging_dir = NULL,
  region_name = NULL,
  bigint = c("integer64", "integer", "numeric", "character"),
  binary = c("raw", "character"),
  json = c("auto", "character"),
  timezone = "UTC",
  keyboard_interrupt = TRUE,
  rstudio_conn_tab = TRUE,
  ...
)
```

Arguments

drv	an object that inherits from DBIDriver , or an existing DBIConnection object (in order to clone an existing connection).
aws_access_key_id	AWS access key ID
aws_secret_access_key	AWS secret access key
aws_session_token	AWS temporary session token
schema_name	The schema_name to which the connection belongs
work_group	The name of the work group to run Athena queries , Currently defaulted to NULL.
poll_interval	Amount of time took when checking query execution status. Default set to a random interval between 0.5 - 1 seconds.

encryption_option	Athena encryption at rest link . Supported Amazon S3 Encryption Options ["NULL", "SSE_S3", "SSE_KMS", "CSE_KMS"]. Connection will default to NULL, usually changing this option is not required.
kms_key	AWS Key Management Service , please refer to link for more information around the concept.
profile_name	The name of a profile to use. If not given, then the default profile is used. To set profile name, the AWS Command Line Interface (AWS CLI) will need to be configured. To configure AWS CLI please refer to: Configuring the AWS CLI .
role_arn	The Amazon Resource Name (ARN) of the role to assume (such as arn:aws:sts::123456789012:assum
role_session_name	An identifier for the assumed role session. By default ‘noctua‘ creates a session name sprintf("noctua-session-%s",as.integer(Sys.time()))
duration_seconds	The duration, in seconds, of the role session. The value can range from 900 seconds (15 minutes) up to the maximum session duration setting for the role. This setting can have a value from 1 hour to 12 hours. By default duration is set to 3600 seconds (1 hour).
s3_staging_dir	The location in Amazon S3 where your query results are stored, such as s3://path/to/query/bucket/
region_name	Default region when creating new connections. Please refer to link for AWS region codes (region code example: Region = EU (Ireland) region_name = "eu-west-1")
bigint	The R type that 64-bit integer types should be mapped to, default is [bit64::integer64], which allows the full range of 64 bit integers.
binary	The R type that [binary/varbinary] types should be mapped to, default is [raw]. If the mapping fails R will resort to [character] type. To ignore data type conversion set to ["character"].
json	Attempt to converts AWS Athena data types [arrays, json] using jsonlite:parse_json. If the mapping fails R will resort to [character] type. Custom Json parsers can be provide by using a function with data frame parameter. To ignore data type conversion set to ["character"].
timezone	Sets the timezone for the connection. The default is ‘UTC‘. If ‘NULL‘ then no timezone is set, which defaults to the server’s time zone. ‘AWS Athena‘ accepted time zones: https://docs.aws.amazon.com/athena/latest/ug/athena-supported-time-zones.html .
keyboard_interrupt	Stops AWS Athena process when R gets a keyboard interrupt, currently defaults to TRUE
rstudio_conn_tab	Optional to get AWS Athena Schema and display it in RStudio’s Connections Tab. Default set to TRUE.
...	other parameters for paws session

Value

dbConnect() returns a s4 class. This object is used to communicate with AWS Athena.

See Also[dbConnect](#)**Examples**

```
## Not run:
# Connect to Athena using your aws access keys
library(DBI)
con <- dbConnect(noctua::athena(),
                  aws_access_key_id='YOUR_ACCESS_KEY_ID', #
                  aws_secret_access_key='YOUR_SECRET_ACCESS_KEY',
                  s3_staging_dir='s3://path/to/query/bucket/',
                  region_name='us-west-2')
dbDisconnect(con)

# Connect to Athena using your profile name
# Profile name can be created by using AWS CLI
con <- dbConnect(noctua::athena(),
                  profile_name = "YOUR_PROFILE_NAME",
                  s3_staging_dir = 's3://path/to/query/bucket/')
dbDisconnect(con)

# Connect to Athena using ARN role
con <- dbConnect(noctua::athena(),
                  profile_name = "YOUR_PROFILE_NAME",
                  role_arn = "arn:aws:sts::123456789012:assumed-role/role_name/role_session_name",
                  s3_staging_dir = 's3://path/to/query/bucket/')

dbDisconnect(con)

## End(Not run)
```

dbConvertTable

*Simple wrapper to convert Athena backend file types***Description**

Utilises AWS Athena to convert AWS S3 backend file types. It also also to create more efficient file types i.e. "parquet" and "orc" from SQL queries.

Usage

```
dbConvertTable(conn, obj, name, ...)
## S4 method for signature 'AthenaConnection'
dbConvertTable(
  conn,
  obj,
  name,
```

```

partition = NULL,
s3.location = NULL,
file.type = c("NULL", "csv", "tsv", "parquet", "json", "orc"),
compress = TRUE,
data = TRUE,
...
)

```

Arguments

conn	An AthenaConnection object, produced by [DBI::dbConnect()]
obj	Athena table or SQL DML query to be converted. For SQL, the query need to be wrapped with DBI::SQL() and follow AWS Athena DML format link
name	Name of destination table
...	Extra parameters, currently not used
partition	Partition Athena table
s3.location	location to store output file, must be in s3 uri format for example ("s3://mybucket/data/").
file.type	File type for name, currently support ["NULL", "csv", "tsv", "parquet", "json", "orc"]. "NULL" will let Athena set the file type for you.
compress	Compress name, currently can only compress ["parquet", "orc"] (AWS Athena CTAS)
data	If name should be created with data or not.

Value

`dbConvertTable()` returns TRUE but invisible.

Examples

```

## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `RAthena::dbConnect` documentation

library(DBI)
library(noctua)

# Demo connection to Athena using profile name
con <- dbConnect(athena())

# write iris table to Athena in defualt delimited format
dbWriteTable(con, "iris", iris)

# convert delimited table to parquet
dbConvertTable(con,
              obj = "iris",
              name = "iris_parquet",
              file.type = "parquet")

```

```

# Create partitioned table from non-partitioned
# iris table using SQL DML query
dbConvertTable(con,
  obj = SQL("select
    iris.*,
    date_format(current_date, '%Y%m%d') as time_stamp
  from iris"),
  name = "iris_orc_partitioned",
  file.type = "orc",
  partition = "time_stamp")

# disconnect from Athena
dbDisconnect(con)

## End(Not run)

```

dbDataType,AthenaDriver,ANY-method*Determine SQL data type of object***Description**

Returns a character string that describes the Athena SQL data type for the `obj` object.

Usage

```

## S4 method for signature 'AthenaDriver,ANY'
dbDataType(dbObj, obj, ...)

## S4 method for signature 'AthenaDriver,list'
dbDataType(dbObj, obj, ...)

## S4 method for signature 'AthenaConnection,ANY'
dbDataType(dbObj, obj, ...)

## S4 method for signature 'AthenaConnection,data.frame'
dbDataType(dbObj, obj, ...)

```

Arguments

- | | |
|--------------------|---|
| <code>dbObj</code> | A object inheriting from DBIDriver or DBIConnection |
| <code>obj</code> | An R object whose SQL type we want to determine. |
| <code>...</code> | Other arguments passed on to methods. |

Value

`dbDataType` returns the Athena type that correspond to the `obj` argument as an non-empty character string.

See Also

[dbDataType](#)

Examples

```
library(noctua)
dbDataType(athena(), 1:5)
dbDataType(athena(), 1)
dbDataType(athena(), TRUE)
dbDataType(athena(), Sys.Date())
dbDataType(athena(), Sys.time())
dbDataType(athena(), c("x", "abc"))
dbDataType(athena(), list(raw(10), raw(20)))

vapply(iris, function(x) dbDataType(noctua::athena(), x),
       FUN.VALUE = character(1), USE.NAMES = TRUE)

## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Sending Queries to Athena
dbDataType(con, iris)

# Disconnect conenction
dbDisconnect(con)

## End(Not run)
```

dbDisconnect

Disconnect (close) an Athena connection

Description

This closes the connection to Athena.

Usage

```
## S4 method for signature 'AthenaConnection'
dbDisconnect(conn, ...)
```

Arguments

- conn A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).
 ... Other parameters passed on to methods.

Value

`dbDisconnect()` returns TRUE, invisibly.

See Also

[dbDisconnect](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Disconnect conenction
dbDisconnect(con)

## End(Not run)
```

`dbExistsTable`

Does Athena table exist?

Description

Returns logical scalar if the table exists or not. TRUE if the table exists, FALSE otherwise.

Usage

```
## S4 method for signature 'AthenaConnection,character'
dbExistsTable(conn, name, ...)
```

Arguments

- conn A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).
 name The table name, passed on to [dbQuoteIdentifier\(\)](#). Options are:
 • a character string with the unquoted DBMS table name, e.g. "table_name",
 • a call to [Id\(\)](#) with components to the fully qualified table name, e.g. `Id(schema = "my_schema", table = "table_name")`

- a call to [SQL\(\)](#) with the quoted and fully qualified table name given verbatim, e.g. `SQL(''my_schema''.table_name'')`
- ... Other parameters passed on to methods.

Value

`dbExistsTable()` returns logical scalar. TRUE if the table exists, FALSE otherwise.

See Also

[dbExistsTable](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Write data.frame to Athena table
dbWriteTable(con, "mtcars", mtcars,
             partition=c("TIMESTAMP" = format(Sys.Date(), "%Y%m%d")),
             s3.location = "s3://mybucket/data/")

# Check if table exists from Athena
dbExistsTable(con, "mtcars")

# Disconnect conenction
dbDisconnect(con)

## End(Not run)
```

dbFetch

Fetch records from previously executed query

Description

Currently returns the top n elements (rows) from result set or returns entire table from Athena.

Usage

```
## S4 method for signature 'AthenaResult'
dbFetch(res, n = -1, ...)
```

Arguments

res	An object inheriting from DBIResult , created by dbSendQuery() .
n	maximum number of records to retrieve per fetch. Use n = -1 or n = Inf to retrieve all pending records. Some implementations may recognize other special values. If entire dataframe is required use n = -1 or n = Inf.
...	Other arguments passed on to methods.

Value

`dbFetch()` returns a data frame.

See Also

[dbFetch](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

res <- dbSendQuery(con, "show databases")
dbFetch(res)
dbClearResult(res)

# Disconnect from Athena
dbDisconnect(con)

## End(Not run)
```

dbGetInfo

Get DBMS metadata

Description

Get DBMS metadata

Usage

```
## S4 method for signature 'AthenaConnection'
dbGetInfo(dbObj, ...)

## S4 method for signature 'AthenaResult'
dbGetInfo(dbObj, ...)
```

Arguments

- `dbObj` An object inheriting from [DBIObject](#), i.e. [DBIDriver](#), [DBIConnection](#), or a [DBIResult](#)
`...` Other arguments to methods.

Value

a named list

See Also

[dbGetInfo](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Returns metadata from connection object
metadata <- dbGetInfo(con)

# Return metadata from Athena query object
res <- dbSendQuery(con, "show databases")
dbGetInfo(res)

# Clear result
dbClearResult(res)

# disconnect from Athena
dbDisconnect(con)

## End(Not run)
```

dbGetPartition *Athena table partitions*

Description

This method returns all partitions from Athena table.

Usage

```
dbGetPartition(conn, name, ..., .format = FALSE)

## S4 method for signature 'AthenaConnection'
dbGetPartition(conn, name, ..., .format = FALSE)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. Id(schema = "my_schema", table = "table_name") • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. SQL('"my_schema"."table_name"')
...	Other parameters passed on to methods.
.format	re-formats AWS Athena partitions format. So that each column represents a partition from the AWS Athena table. Default set to FALSE to prevent breaking previous package behaviour.

Value

data.frame that returns all partitions in table, if no partitions in Athena table then function will return error from Athena.

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# write iris table to Athena
dbWriteTable(con, "iris",
            iris,
            partition = c("timestamp" = format(Sys.Date(), "%Y%m%d")),
            s3.location = "s3://path/to/store/athena/table/")

# return table partitions
noctua::dbGetPartition(con, "iris")

# disconnect from Athena
dbDisconnect(con)

## End(Not run)
```

dbGetQuery*Send query, retrieve results and then clear result set***Description**

Send query, retrieve results and then clear result set

Usage

```
## S4 method for signature 'AthenaConnection,character'
dbGetQuery(conn, statement, statistics = FALSE, unload = athena_unload(), ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by dbConnect() .
<code>statement</code>	a character string containing SQL.
<code>statistics</code>	If set to TRUE will print out AWS Athena statistics of query.
<code>unload</code>	boolean input to modify ‘statement’ to align with AWS Athena UNLOAD , default is set to FALSE.
...	Other parameters passed on to methods.

Value

`dbGetQuery()` returns a dataframe.

Note

If the user does not have permission to remove AWS S3 resource from AWS Athena output location, then an AWS warning will be returned. It is better use query caching [noctua_options](#) so that the warning doesn’t repeatedly show.

See Also

[dbGetQuery](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())
```

```
# Sending Queries to Athena  
dbGetQuery(con, "show databases")  
  
# Disconnect connection  
dbDisconnect(con)  
  
## End(Not run)
```

dbGetStatement	<i>Get the statement associated with a result set</i>
----------------	---

Description

Returns the statement that was passed to [dbSendQuery()] or [dbSendStatement()].

Usage

```
## S4 method for signature 'AthenaResult'  
dbGetStatement(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

dbGetStatement() returns a character.

See Also

[dbGetStatement](#)

Examples

```
## Not run:  
# Note:  
# - Require AWS Account to run below example.  
# - Different connection methods can be used please see `noctua::dbConnect` documentation  
  
library(DBI)  
  
# Demo connection to Athena using profile name  
con <- dbConnect(noctua::athena())  
  
rs <- dbSendQuery(con, "SHOW TABLES in default")  
dbGetStatement(rs)  
  
## End(Not run)
```

dbGetTables*List Athena Schema, Tables and Table Types***Description**

Method to get Athena schema, tables and table types return as a data.frame

Usage

```
dbGetTables(conn, ...)
## S4 method for signature 'AthenaConnection'
dbGetTables(conn, schema = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
...	Other parameters passed on to methods.
schema	Athena schema, default set to NULL to return all tables from all Athena schemas. Note: The use of DATABASE and SCHEMA is interchangeable within Athena.

Value

`dbGetTables()` returns a data.frame.

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)
library(noctua)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Return hierarchy of tables in Athena
dbGetTables(con)

# Disconnect conenction
dbDisconnect(con)

## End(Not run)
```

dbHasCompleted	<i>Completion status</i>
----------------	--------------------------

Description

This method returns if the query has completed.

Usage

```
## S4 method for signature 'AthenaResult'  
dbHasCompleted(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbHasCompleted()` returns a logical scalar. TRUE if the query has completed, FALSE otherwise.

See Also

[dbHasCompleted](#)

Examples

```
## Not run:  
# Note:  
# - Require AWS Account to run below example.  
# - Different connection methods can be used please see `noctua::dbConnect` documentation  
  
library(DBI)  
  
# Demo connection to Athena using profile name  
con <- dbConnect(noctua::athena())  
  
# Check if query has completed  
res <- dbSendQuery(con, "show databases")  
dbHasCompleted(res)  
  
dbClearResult(res)  
  
# Disconnect from Athena  
dbDisconnect(con)  
  
## End(Not run)
```

dbIsValid	<i>Is this DBMS object still valid?</i>
-----------	---

Description

This method tests whether the dbObj is still valid.

Usage

```
## S4 method for signature 'AthenaConnection'
dbIsValid(dbObj, ...)

## S4 method for signature 'AthenaResult'
dbIsValid(dbObj, ...)
```

Arguments

dbObj	An object inheriting from DBObject , i.e. DBIDriver , DBIConnection , or a DBIResult
...	Other arguments to methods.

Value

`dbIsValid()` returns logical scalar, TRUE if the object (dbObj) is valid, FALSE otherwise.

See Also

[dbIsValid](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Check is connection is valid
dbIsValid(con)

# Check is query is valid
res <- dbSendQuery(con, "show databases")
dbIsValid(res)

# Check if query is valid after clearing result
```

```

dbClearResult(res)
dbIsValid(res)

# Check if connection is valid after closing connection
dbDisconnect(con)
dbIsValid(con)

## End(Not run)

```

dbListFields*List Field names of Athena table***Description**

List Field names of Athena table

Usage

```

## S4 method for signature 'AthenaConnection,character'
dbListFields(conn, name, ...)

```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. Id(schema = "my_schema", table = "table_name") • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. SQL('"my_schema"."table_name"')
...	Other parameters passed on to methods.

Value

`dbListFields()` returns a character vector with all the fields from an Athena table.

See Also

[dbListFields](#)

Examples

```

## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

```

```
# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Write data.frame to Athena table
dbWriteTable(con, "mtcars", mtcars,
             partition=c("TIMESTAMP" = format(Sys.Date(), "%Y%m%d")),
             s3.location = "s3://mybucket/data/")

# Return list of fields in table
dbListFields(con, "mtcars")

# Disconnect conenction
dbDisconnect(con)

## End(Not run)
```

dbListTables*List Athena Tables***Description**

Returns the unquoted names of Athena tables accessible through this connection.

Usage

```
## S4 method for signature 'AthenaConnection'
dbListTables(conn, schema = NULL, ...)
```

Arguments

- conn** A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).
- schema** Athena schema, default set to NULL to return all tables from all Athena schemas.
Note: The use of DATABASE and SCHEMA is interchangeable within Athena.
- ...** Other parameters passed on to methods.

Value

`dbListTables()` returns a character vector with all the tables from Athena.

See Also

[dbListTables](#)

Examples

```
## Not run:  
# Note:  
# - Require AWS Account to run below example.  
# - Different connection methods can be used please see `noctua::dbConnect` documentation  
  
library(DBI)  
  
# Demo connection to Athena using profile name  
con <- dbConnect(noctua::athena())  
  
# Return list of tables in Athena  
dbListTables(con)  
  
# Disconnect conenction  
dbDisconnect(con)  
  
## End(Not run)
```

dbplyr_edition *Declare which version of dbplyr API is being called.*

Description

Declare which version of dbplyr API is being called.

Usage

```
dbplyr_edition.AthenaConnection(con)
```

Arguments

con A [dbConnect](#) object, as returned by `dbConnect()`

Value

Integer for which version of ‘dbplyr’ is going to be used.

dbQuote

*Quote Identifiers***Description**

Call this method to generate string that is suitable for use in a query as a column or table name.

Usage

```
## S4 method for signature 'AthenaConnection,character'
dbQuoteString(conn, x, ...)

## S4 method for signature 'AthenaConnection,POSIXct'
dbQuoteString(conn, x, ...)

## S4 method for signature 'AthenaConnection,Date'
dbQuoteString(conn, x, ...)

## S4 method for signature 'AthenaConnection,SQL'
dbQuoteIdentifier(conn, x, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
x	A character vector to quote as string.
...	Other arguments passed on to methods.

Value

Returns a character object, for more information please check out: [dbQuoteString](#), [dbQuoteIdentifier](#)

See Also

[dbQuoteString](#), [dbQuoteIdentifier](#)

dbRemoveTable

*Remove table from Athena***Description**

Removes Athena table but does not remove the data from Amazon S3 bucket.

Usage

```
## S4 method for signature 'AthenaConnection,character'
dbRemoveTable(conn, name, delete_data = TRUE, confirm = FALSE, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. Id(schema = "my_schema", table = "table_name") • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. SQL('"my_schema"."table_name"')
delete_data	Deletes S3 files linking to AWS Athena table
confirm	Allows for S3 files to be deleted without the prompt check. It is recommended to leave this set to FALSE to avoid deleting other S3 files when the table's definition points to the root of S3 bucket.
...	Other parameters passed on to methods.

Value

`dbRemoveTable()` returns TRUE, invisibly.

Note

If you are having difficulty removing AWS S3 files please check if the AWS S3 location following AWS best practices: [Table Location in Amazon S3](#)

See Also

[dbRemoveTable](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Write data.frame to Athena table
dbWriteTable(con, "mtcars", mtcars,
            partition=c("TIMESTAMP" = format(Sys.Date(), "%Y%m%d")),
            s3.location = "s3://mybucket/data/")

# Remove Table from Athena
dbRemoveTable(con, "mtcars")

# Disconnect connection
dbDisconnect(con)
```

```
## End(Not run)
```

dbShow*Show Athena table's DDL***Description**

Executes a statement to return the data description language (DDL) of the Athena table.

Usage

```
dbShow(conn, name, ...)
## S4 method for signature 'AthenaConnection'
dbShow(conn, name, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. <code>Id(schema = "my_schema", table = "table_name")</code> • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. <code>SQL('\"my_schema\".\"table_name\"')</code>
...	Other parameters passed on to methods.

Value

`dbShow()` returns [SQL](#) characters of the Athena table DDL.

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# write iris table to Athena
dbWriteTable(con, "iris",
            iris,
            partition = c("timestamp" = format(Sys.Date(), "%Y%m%d")),
```

```
s3.location = "s3://path/to/store/athena/table/")

# return table ddl
noctua::dbShow(con, "iris")

# disconnect from Athena
dbDisconnect(con)

## End(Not run)
```

dbStatistics*Show AWS Athena Statistics*

Description

Returns AWS Athena Statistics from execute queries [dbSendQuery](#)

Usage

```
dbStatistics(res, ...)

## S4 method for signature 'AthenaResult'
dbStatistics(res, ...)
```

Arguments

res An object inheriting from [DBIResult](#).
... Other arguments passed on to methods.

Value

`dbStatistics()` returns list containing Athena Statistics return from paws.

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `RAthena::dbConnect` documentation

library(DBI)
library(noctua)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

res <- dbSendQuery(con, "show databases")
dbStatistics(res)
```

```
# Clean up
dbClearResult(res)

## End(Not run)
```

db_compute

S3 implementation of db_compute for Athena This is a backend function for dplyr's compute function. Users won't be required to access and run this function.

Description

S3 implementation of db_compute for Athena

This is a backend function for dplyr's compute function. Users won't be required to access and run this function.

Usage

```
db_compute.AthenaConnection(con, table, sql, ...)
```

Arguments

con	A dbConnect object, as returned by <code>dbConnect()</code>
table	Table name, if left default noctua will use the default from dplyr's compute function.
sql	SQL code to be sent to the data
...	passes noctua table creation parameters: [file_type,s3_location,partition] <ul style="list-style-type: none"> • file_type: What file type to store data.frame on s3, noctua currently supports ["NULL","csv", "parquet", "json"]. "NULL" will let Athena set the file_type for you. • s3_location: s3 bucket to store Athena table, must be set as a s3 uri for example ("s3://mybucket/data/") • partition: Partition Athena table, requires to be a partitioned variable from previous table.

Value

`db_compute` returns table name

See Also

[AthenaWriteTables](#) [backend_dbplyr_v2](#) [backend_dbplyr_v1](#)

Examples

```

## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)
library(dplyr)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Write data.frame to Athena table
copy_to(con, mtcars,
        s3_location = "s3://mybucket/data/")

# Write Athena table from tbl_sql
athena_mtcars <- tbl(con, "mtcars")
mtcars_filter <- athena_mtcars %>% filter(gear >=4)

# create athena with unique table name
mtcars_filer %>%
  compute()

# create athena with specified name and s3 location
mtcars_filer %>%
  compute("mtcars_filer",
         s3_location = "s3://mybucket/mtcars_filer/")

# Disconnect from Athena
dbDisconnect(con)

## End(Not run)

```

db_connection_describe

S3 implementation of db_connection_describe for Athena (api version 2).

Description

This is a backend function for dplyr to retrieve meta data about Athena queries. Users won't be required to access and run this function.

Usage

```
db_connection_describe.AthenaConnection(con)
```

Arguments

<code>con</code>	A dbConnect object, as returned by <code>dbConnect()</code>
------------------	---

Value

Character variable containing Meta Data about query sent to Athena. The Meta Data is returned in the following format:

```
"Athena <paws version> [<profile_name>@region/database]"
```

db_copy_to

S3 implementation of db_copy_to for Athena

Description

This is an Athena method for dbplyr function `db_copy_to` to create an Athena table from a `data.frame`.

Usage

```
db_copy_to.AthenaConnection(
  con,
  table,
  values,
  overwrite = FALSE,
  append = FALSE,
  types = NULL,
  partition = NULL,
  s3_location = NULL,
  file_type = c("csv", "tsv", "parquet"),
  compress = FALSE,
  max_batch = Inf,
  ...
)
```

Arguments

<code>con</code>	A dbConnect object, as returned by <code>dbConnect()</code>
<code>table</code>	A character string specifying a table name. Names will be automatically quoted so you can use any sequence of characters, not just any valid bare table name.
<code>values</code>	A <code>data.frame</code> to write to the database.
<code>overwrite</code>	Allows overwriting the destination table. Cannot be TRUE if <code>append</code> is also TRUE.
<code>append</code>	Allow appending to the destination table. Cannot be TRUE if <code>overwrite</code> is also TRUE. Existing Athena DDL file type will be retained and used when uploading data to AWS Athena. If parameter <code>file.type</code> doesn't match AWS Athena DDL file type a warning message will be created notifying user and noctua will use the file type for the Athena DDL.

types	Additional field types used to override derived types.
partition	Partition Athena table (needs to be a named list or vector) for example: c(var1 = "2019-20-13")
s3_location	s3 bucket to store Athena table, must be set as a s3 uri for example ("s3://mybucket/data/")
file_type	What file type to store data.frame on s3, noctua currently supports ["tsv", "csv", "parquet"]. Default delimited file type is "tsv", in previous versions of noctua (<= 1.4.0) file type "csv" was used as default. The reason for the change is that columns containing Array/JSON format cannot be written to Athena due to the separating value ",". This would cause issues with AWS Athena. Note: "parquet" format is supported by the arrow package and it will need to be installed to utilise the "parquet" format.
compress	FALSE TRUE To determine if to compress file.type. If file type is ["csv", "tsv"] then "gzip" compression is used, for file type "parquet" "snappy" compression is used.
max_batch	Split the data frame by max number of rows i.e. 100,000 so that multiple files can be uploaded into AWS S3. By default when compression is set to TRUE and file.type is "csv" or "tsv" max.batch will split data.frame into 20 batches. This is to help the performance of AWS Athena when working with files compressed in "gzip" format. max.batch will not split the data.frame when loading file in parquet format. For more information please go to link
...	other parameters currently not supported in noctua

Value

db_copy_to returns table name

See Also

[AthenaWriteTables](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)
library(dplyr)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# List existing tables in Athena
dbListTables(con)

# Write data.frame to Athena table
copy_to(con, mtcars,
       s3_location = "s3://mybucket/data/")
```

```

# Checking if uploaded table exists in Athena
dbExistsTable(con, "mtcars")

# Write Athena table from tbl_sql
athena_mtcars <- tbl(con, "mtcars")
mtcars_filter <- athena_mtcars %>% filter(gear >=4)

copy_to(con, mtcars_filter)

# Checking if uploaded table exists in Athena
dbExistsTable(con, "mtcars_filter")

# Disconnect from Athena
dbDisconnect(con)

## End(Not run)

```

db_desc*S3 implementation of db_desc for Athena (api version 1).*

Description

This is a backend function for dplyr to retrieve meta data about Athena queries. Users won't be required to access and run this function.

Usage

```
db_desc.AthenaConnection(x)
```

Arguments

x	A dbConnect object, as returned by <code>dbConnect()</code>
---	---

Value

Character variable containing Meta Data about query sent to Athena. The Meta Data is returned in the following format:

```
"Athena <paws version> [<profile_name>@region/database]"
```

noctua_options	<i>A method to configure noctua backend options.</i>
----------------	--

Description

noctua_options() provides a method to change the backend. This includes changing the file parser, whether noctua should cache query ids locally and number of retries on a failed api call.

Usage

```
noctua_options(  
  file_parser,  
  bigint,  
  binary,  
  json,  
  cache_size,  
  clear_cache,  
  retry,  
  retry_quiet,  
  unload,  
  verbose  
)
```

Arguments

file_parser	Method to read and write tables to Athena, currently default to "data.table". The file_parser also determines the data format returned for example "data.table" will return data.table and "vroom" will return tibble.
bigint	The R type that 64-bit integer types should be mapped to (default: "integer64"). Inbuilt bigint conversion types ["integer64", "integer", "numeric", "character"].
binary	The R type that [binary/varbinary] types should be mapped to (default "raw"). Inbuilt binary conversion types ["raw", "character"].
json	Attempt to converts AWS Athena data types [arrays, json] using jsonlite::parse_json (default: "auto"). Inbuilt json conversion types ["auto", "character"]. Custom Json parsers can be provide by using a function with data frame parameter.
cache_size	Number of queries to be cached. Currently only support caching up to 100 distinct queries (default: 0).
clear_cache	Clears all previous cached query metadata
retry	Maximum number of requests to attempt (default: 5).
retry_quiet	This method is deprecated please use verbose instead.
unload	set AWS Athena unload functionality globally (default: FALSE)
verbose	print package info messages (default: TRUE)

Value

`noctua_options()` returns NULL, invisibly.

Examples

```
library(noctua)

# change file parser from default data.table to vroom
noctua_options("vroom")

# cache queries locally
noctua_options(cache_size = 5)
```

Query

*Execute a query on Athena***Description**

The `dbSendQuery()` and `dbSendStatement()` method submits a query to Athena but does not wait for query to execute. `dbHasCompleted` method will need to ran to check if query has been completed or not. The `dbExecute()` method submits a query to Athena and waits for the query to be executed.

Usage

```
## S4 method for signature 'AthenaConnection,character'
dbSendQuery(conn, statement, unload = athena_unload(), ...)

## S4 method for signature 'AthenaConnection,character'
dbSendStatement(conn, statement, unload = athena_unload(), ...)

## S4 method for signature 'AthenaConnection,character'
dbExecute(conn, statement, unload = athena_unload(), ...)
```

Arguments

<code>conn</code>	A <code>DBIConnection</code> object, as returned by <code>dbConnect()</code> .
<code>statement</code>	a character string containing SQL.
<code>unload</code>	boolean input to modify ‘statement’ to align with AWS Athena UNLOAD , default is set to FALSE.
<code>...</code>	Other parameters passed on to methods.

Value

Returns `AthenaResult` s4 class.

See Also

[dbSendQuery](#), [dbSendStatement](#), [dbExecute](#)

Examples

```
## Not run:  
# Note:  
# - Require AWS Account to run below example.  
# - Different connection methods can be used please see `noctua::dbConnect` documentation  
  
library(DBI)  
  
# Demo connection to Athena using profile name  
con <- dbConnect(noctua::athena())  
  
# Sending Queries to Athena  
res1 <- dbSendQuery(con, "show databases")  
res2 <- dbSendStatement(con, "show databases")  
res3 <- dbExecute(con, "show databases")  
  
# Disconnect conenction  
dbDisconnect(con)  
  
## End(Not run)
```

session_token

Get Session Tokens for PAWS Connection

Description

Returns a set of temporary credentials for an AWS account or IAM user ([link](#)).

Usage

```
get_session_token(  
  profile_name = NULL,  
  region_name = NULL,  
  serial_number = NULL,  
  token_code = NULL,  
  duration_seconds = 3600L,  
  set_env = FALSE  
)
```

Arguments

profile_name	The name of a profile to use. If not given, then the default profile is used. To set profile name, the AWS Command Line Interface (AWS CLI) will need to be configured. To configure AWS CLI please refer to: Configuring the AWS CLI .
--------------	---

<code>region_name</code>	Default region when creating new connections. Please refer to link for AWS region codes (region code example: Region = EU (Ireland) <code>region_name = "eu-west-1"</code>)
<code>serial_number</code>	The identification number of the MFA device that is associated with the IAM user who is making the GetSessionToken call. Specify this value if the IAM user has a policy that requires MFA authentication. The value is either the serial number for a hardware device (such as 'GAHT12345678') or an Amazon Resource Name (ARN) for a virtual device (such as <code>arn:aws:iam::123456789012:mfa/user</code>).
<code>token_code</code>	The value provided by the MFA device, if MFA is required. If any policy requires the IAM user to submit an MFA code, specify this value. If MFA authentication is required, the user must provide a code when requesting a set of temporary security credentials. A user who fails to provide the code receives an "access denied" response when requesting resources that require MFA authentication.
<code>duration_seconds</code>	The duration, in seconds, that the credentials should remain valid. Acceptable duration for IAM user sessions range from 900 seconds (15 minutes) to 129,600 seconds (36 hours), with 3,600 seconds (1 hour) as the default.
<code>set_env</code>	If set to TRUE environmental variables <code>AWS_ACCESS_KEY_ID</code> , <code>AWS_SECRET_ACCESS_KEY</code> and <code>AWS_SESSION_TOKEN</code> will be set.

Value

`get_session_token()` returns a list containing: "AccessKeyId", "SecretAccessKey", "SessionToken" and "Expiration"

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.

library(noctua)
library(DBI)

# Create Temporary Credentials duration 1 hour
get_session_token("YOUR_PROFILE_NAME",
                   serial_number='arn:aws:iam::123456789012:mfa/user',
                   token_code = "531602",
                   set_env = TRUE)

# Connect to Athena using temporary credentials
con <- dbConnect(athena())

## End(Not run)
```

sqlCreateTable	<i>Creates query to create a simple Athena table</i>
----------------	--

Description

Creates an interface to compose CREATE EXTERNAL TABLE.

Usage

```
## S4 method for signature 'AthenaConnection'
sqlCreateTable(
  con,
  table,
  fields,
  field.types = NULL,
  partition = NULL,
  s3.location = NULL,
  file.type = c("tsv", "csv", "parquet", "json"),
  compress = FALSE,
  ...
)
```

Arguments

con	A database connection.
table	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. Id(schema = "my_schema", table = "table_name") • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. SQL('"my_schema"."table_name"')
fields	Either a character vector or a data frame. A named character vector: Names are column names, values are types. Names are escaped with dbQuoteIdentifier() . Field types are unescaped. A data frame: field types are generated using dbDataType() .
field.types	Additional field types used to override derived types.
partition	Partition Athena table (needs to be a named list or vector) for example: c(var1 = "2019-20-13")
s3.location	s3 bucket to store Athena table, must be set as a s3 uri for example ("s3://mybucket/data/"). By default s3.location is set s3 staging directory from AthenaConnection object.
file.type	What file type to store data.frame on s3, noctua currently supports ["tsv", "csv", "parquet", "json"]. Default delimited file type is "tsv", in previous versions of noctua (<= 1.4.0) file type "csv" was used as default. The reason for the

	change is that columns containing Array/JSON format cannot be written to Athena due to the separating value ",". This would cause issues with AWS Athena. Note: "parquet" format is supported by the arrow package and it will need to be installed to utilise the "parquet" format. "json" format is supported by jsonlite package and it will need to be installed to utilise the "json" format.
compress	FALSE TRUE To determine if to compress file.type. If file type is ["csv", "tsv"] then "gzip" compression is used, for file type "parquet" "snappy" compression is used. Currently noctua doesn't support compression for "json" file type.
...	Other arguments used by individual methods.

Value

`sqlCreateTable` returns data.frame's DDL in the [SQL](#) format.

See Also

[sqlCreateTable](#)

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(DBI)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())

# Create DDL for iris data.frame
sqlCreateTable(con, "iris", iris, s3.location = "s3://path/to/athena/table")

# Create DDL for iris data.frame with partition
sqlCreateTable(con, "iris", iris,
               partition = "timestamp",
               s3.location = "s3://path/to/athena/table")

# Create DDL for iris data.frame with partition and file.type parquet
sqlCreateTable(con, "iris", iris,
               partition = "timestamp",
               s3.location = "s3://path/to/athena/table",
               file.type = "parquet")

# Disconnect from Athena
dbDisconnect(con)

## End(Not run)
```

sqlData	<i>Converts data frame into suitable format to be uploaded to Athena</i>
---------	--

Description

This method converts data.frame columns into the correct format so that it can be uploaded Athena.

Usage

```
## S4 method for signature 'AthenaConnection'  
sqlData(  
  con,  
  value,  
  row.names = NA,  
  file.type = c("tsv", "csv", "parquet", "json"),  
  ...  
)
```

Arguments

con	A database connection.
value	A data frame
row.names	Either TRUE, FALSE, NA or a string. If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector. A string is equivalent to TRUE, but allows you to override the default name. For backward compatibility, NULL is equivalent to FALSE.
file.type	What file type to store data.frame on s3, noctua currently supports ["csv", "tsv", "parquet", "json"]. Note: This parameter is used for format any special characters that clash with file type separator.
...	Other arguments used by individual methods.

Value

sqlData returns a dataframe formatted for Athena. Currently converts list variable types into character split by '|', similar to how data.table writes out to files.

See Also

[sqlData](#)

<code>sql_translate_env</code>	<i>AWS Athena backend dbplyr version 1 and 2</i>
--------------------------------	--

Description

Create s3 implementation of `sql_translate_env` for AWS Athena sql translate environment based off [Athena Data Types](#) and [DML Queries, Functions, and Operators](#)

Usage

```
sql_translator.AthenaConnection(con)

sql_translate_env.AthenaConnection(con)

sql_escape_string.AthenaConnection(con, x)
```

Arguments

<code>con</code>	An AthenaConnection object, produced by [DBI::dbConnect()]
<code>x</code>	An object to escape. Existing sql vectors will be left as is, character vectors are escaped with single quotes, numeric vectors have trailing ‘.0‘ added if they’re whole numbers, identifiers are escaped with double quotes.

<code>work_group</code>	<i>Athena Work Groups</i>
-------------------------	---------------------------

Description

Lower level API access, allows user to create and delete Athena Work Groups.

create_work_group Creates a workgroup with the specified name ([link](#)). The work group utilises parameters from the dbConnect object, to determine the encryption and output location of the work group. The s3_staging_dir, encryption_option and kms_key parameters are gotten from [dbConnect](#)

tag_options Helper function to create tag options for function `create_work_group()`

delete_work_group Deletes the workgroup with the specified name ([link](#)). The primary work-group cannot be deleted.

list_work_groups Lists available workgroups for the account ([link](#)).

get_work_group Returns information about the workgroup with the specified name ([link](#)).

update_work_group Updates the workgroup with the specified name ([link](#)). The workgroup’s name cannot be changed. The work group utilises parameters from the dbConnect object, to determine the encryption and output location of the work group. The s3_staging_dir, encryption_option and kms_key parameters are gotten from [dbConnect](#)

Usage

```
create_work_group(  
  conn,  
  work_group = NULL,  
  enforce_work_group_config = FALSE,  
  publish_cloud_watch_metrics = FALSE,  
  bytes_scanned_cut_off = 10000000L,  
  description = NULL,  
  tags = tag_options(key = NULL, value = NULL)  
)  
  
tag_options(key = NULL, value = NULL)  
  
delete_work_group(conn, work_group = NULL, recursive_delete_option = FALSE)  
  
list_work_groups(conn)  
  
get_work_group(conn, work_group = NULL)  
  
update_work_group(  
  conn,  
  work_group = NULL,  
  remove_output_location = FALSE,  
  enforce_work_group_config = FALSE,  
  publish_cloud_watch_metrics = FALSE,  
  bytes_scanned_cut_off = 10000000L,  
  description = NULL,  
  state = c("ENABLED", "DISABLED")  
)
```

Arguments

conn	A dbConnect object, as returned by <code>dbConnect()</code>
work_group	The Athena workgroup name.
enforce_work_group_config	If set to TRUE, the settings for the workgroup override client-side settings. If set to FALSE, client-side settings are used. For more information, see Workgroup Settings Override Client-Side Settings .
publish_cloud_watch_metrics	Indicates that the Amazon CloudWatch metrics are enabled for the workgroup.
bytes_scanned_cut_off	The upper data usage limit (cutoff) for the amount of bytes a single query in a workgroup is allowed to scan.
description	The workgroup description.
tags	A tag that you can add to a resource. A tag is a label that you assign to an AWS Athena resource (a workgroup). Each tag consists of a key and an optional value, both of which you define. Tags enable you to categorize workgroups in

Athena, for example, by purpose, owner, or environment. Use a consistent set of tag keys to make it easier to search and filter workgroups in your account. The maximum tag key length is 128 Unicode characters in UTF-8. The maximum tag value length is 256 Unicode characters in UTF-8. You can use letters and numbers representable in UTF-8, and the following characters: "+ -= . _ : / @". Tag keys and values are case-sensitive. Tag keys must be unique per resource. Please use the helper function `tag_options()` to create tags for work group, if no tags are required please put NULL for this parameter.

<code>key</code>	A tag key. The tag key length is from 1 to 128 Unicode characters in UTF-8. You can use letters and numbers representable in UTF-8, and the following characters: "+ -= . _ : / @". Tag keys are case-sensitive and must be unique per resource.
<code>value</code>	A tag value. The tag value length is from 0 to 256 Unicode characters in UTF-8. You can use letters and numbers representable in UTF-8, and the following characters: "+ -= . _ : / @". Tag values are case-sensitive.
<code>recursive_delete_option</code>	The option to delete the workgroup and its contents even if the workgroup contains any named queries
<code>remove_output_location</code>	If set to TRUE, indicates that the previously-specified query results location (also known as a client-side setting) for queries in this workgroup should be ignored and set to null. If set to FALSE the out put location in the workgroup's result configuration will be updated with the new value. For more information, see Workgroup Settings Override Client-Side Settings .
<code>state</code>	The workgroup state that will be updated for the given workgroup.

Value

- `create_work_group`** Returns NULL but invisible
- `tag_options`** Returns list but invisible
- `delete_work_group`** Returns NULL but invisible
- `list_work_groups`** Returns list of available work groups
- `get_work_group`** Returns list of work group meta data
- `update_work_group`** Returns NULL but invisible

Examples

```
## Not run:
# Note:
# - Require AWS Account to run below example.
# - Different connection methods can be used please see `noctua::dbConnect` documentation

library(noctua)

# Demo connection to Athena using profile name
con <- dbConnect(noctua::athena())
```

```
# List current work group available
list_work_groups(con)

# Create a new work group
wg <- create_work_group(
    "demo_work_group",
    description = "This is a demo work group",
    tags = tag_options(key= "demo_work_group", value = "demo_01"))

# List work groups to see new work group
list_work_groups(con)

# get meta data from work group
wg <- get_work_group(con, "demo_work_group")

# Update work group
wg <- update_work_group(con, "demo_work_group",
    description = "This is a demo work group update")

# get updated meta data from work group
wg <- get_work_group(con, "demo_work_group")

# Delete work group
delete_work_group(con, "demo_work_group")

# Disconnect from Athena
dbDisconnect(con)

## End(Not run)
```

Index

assume_role, 3
athena, 5
AthenaConnection, 6, 7, 16, 45, 48
AthenaWriteTables, 5, 36, 39

backend_dbplyr_v1, 9, 36
backend_dbplyr_v2, 9, 36

create_work_group (work_group), 48

db_compute, 36
db_connection_describe, 37
db_copy_to, 38
db_desc, 40
db_explain.AthenaConnection
 (backend_dbplyr_v1), 9
db_query_fields.AthenaConnection
 (backend_dbplyr_v1), 9
dbClearResult, 10
dbClearResult,AthenaResult-method
 (dbClearResult), 10
dbColumnInfo, 11
dbColumnInfo,AthenaResult-method
 (dbColumnInfo), 11
dbConnect, 4, 5, 9, 10, 15, 31, 36, 38, 40, 48,
 49
dbConnect
 (dbConnect,AthenaDriver-method),
 12
dbConnect(), 19, 23, 24, 26, 29, 30, 32–34, 42
dbConnect,AthenaDriver-method, 12
dbConvertTable, 15
dbConvertTable,AthenaConnection-method
 (dbConvertTable), 15
dbDataType, 18
dbDataType
 (dbDataType,AthenaDriver,ANY-method), 17
dbDataType(), 45

dbDataType,AthenaConnection,ANY-method
 (dbDataType,AthenaDriver,ANY-method),
 17
dbDataType,AthenaConnection,data.frame-method
 (dbDataType,AthenaDriver,ANY-method),
 17
dbDataType,AthenaDriver,ANY-method, 17
dbDataType,AthenaDriver,list-method
 (dbDataType,AthenaDriver,ANY-method),
 17
dbDisconnect, 18, 19
dbDisconnect,AthenaConnection-method
 (dbDisconnect), 18
dbExecute, 43
dbExecute,AthenaConnection,character-method
 (Query), 42
dbExistsTable, 19, 20
dbExistsTable,AthenaConnection,character-method
 (dbExistsTable), 19
dbFetch, 20, 21
dbFetch,AthenaResult-method (dbFetch),
 20
dbGetInfo, 21, 22
dbGetInfo,AthenaConnection-method
 (dbGetInfo), 21
dbGetInfo,AthenaResult-method
 (dbGetInfo), 21
dbGetPartition, 22
dbGetPartition,AthenaConnection-method
 (dbGetPartition), 22
dbGetQuery, 24, 24
dbGetQuery,AthenaConnection,character-method
 (dbGetQuery), 24
dbGetStatement, 25, 25
dbGetStatement,AthenaResult-method
 (dbGetStatement), 25
dbGetTables, 26
dbGetTables,AthenaConnection-method
 (dbGetTables), 26

dbHasCompleted, [12](#), [27](#), [27](#), [42](#)
dbHasCompleted,AthenaResult-method
 (dbHasCompleted), [27](#)
DBIConnection, [13](#), [17](#), [19](#), [22–24](#), [26](#), [28–30](#),
 [32–34](#), [42](#)
DBIDriver, [13](#), [17](#), [22](#), [28](#)
DBIObject, [22](#), [28](#)
DBIResult, [10](#), [11](#), [21](#), [22](#), [25](#), [27](#), [28](#), [35](#)
dbIsValid, [11](#), [28](#), [28](#)
dbIsValid,AthenaConnection-method
 (dbIsValid), [28](#)
dbIsValid,AthenaResult-method
 (dbIsValid), [28](#)
dbListFields, [29](#), [29](#)
dbListFields,AthenaConnection,character-method
 (dbListFields), [29](#)
dbListTables, [30](#), [30](#)
dbListTables,AthenaConnection-method
 (dbListTables), [30](#)
dbplyr_edition, [31](#)
dbQuote, [32](#)
dbQuoteIdentifier, [32](#)
dbQuoteIdentifier(), [19](#), [23](#), [29](#), [33](#), [34](#), [45](#)
dbQuoteIdentifier,AthenaConnection,SQL-method
 (dbQuote), [32](#)
dbQuoteString, [32](#)
dbQuoteString,AthenaConnection,character-method
 (dbQuote), [32](#)
dbQuoteString,AthenaConnection,Date-method
 (dbQuote), [32](#)
dbQuoteString,AthenaConnection,POSIXct-method
 (dbQuote), [32](#)
dbRemoveTable, [32](#), [33](#)
dbRemoveTable,AthenaConnection,character-method
 (dbRemoveTable), [32](#)
dbSendQuery, [35](#), [43](#)
dbSendQuery(), [21](#)
dbSendQuery,AthenaConnection,character-method
 (Query), [42](#)
dbSendStatement, [43](#)
dbSendStatement,AthenaConnection,character-method
 (Query), [42](#)
dbShow, [34](#)
dbShow,AthenaConnection-method
 (dbShow), [34](#)
dbStatistics, [35](#)
dbStatistics,AthenaResult-method
 (dbStatistics), [35](#)
dbWriteTable, [8](#)
dbWriteTable,AthenaConnection,character,data.frame-method
 (AthenaWriteTables), [5](#)
dbWriteTable,AthenaConnection,Id,data.frame-method
 (AthenaWriteTables), [5](#)
dbWriteTable,AthenaConnection,SQL,data.frame-method
 (AthenaWriteTables), [5](#)
delete_work_group (work_group), [48](#)
get_session_token (session_token), [43](#)
get_work_group (work_group), [48](#)
Id(), [19](#), [23](#), [29](#), [33](#), [34](#), [45](#)
list_work_groups (work_group), [48](#)
noctua (noctua-package), [3](#)
noctua-package, [3](#)
noctua_options, [11](#), [24](#), [41](#)
Query, [42](#)
session_token, [43](#)
SQL, [34](#), [46](#)
SQL(), [20](#), [23](#), [29](#), [33](#), [34](#), [45](#)
sql_escape_date.AthenaConnection
 (backend_dbplyr_v2), [9](#)
sql_escape_datetime.AthenaConnection
 (backend_dbplyr_v2), [9](#)
sql_escape_string.AthenaConnection
 (sql_translate_env), [48](#)
sql_query_explain.AthenaConnection
 (backend_dbplyr_v2), [9](#)
sql_query_fields.AthenaConnection
 (backend_dbplyr_v2), [9](#)
sql_translate_env, [48](#)
sql_translation.AthenaConnection
 (sql_translate_env), [48](#)
sqlCreateTable, [45](#), [46](#)
sqlCreateTable,AthenaConnection-method
 (sqlCreateTable), [45](#)
sqlData, [47](#), [47](#)
sqlData,AthenaConnection-method
 (sqlData), [47](#)
tag_options (work_group), [48](#)
update_work_group (work_group), [48](#)
work_group, [48](#)