

# Package ‘MatrixLDA’

January 20, 2025

**Type** Package

**Title** Penalized Matrix-Normal Linear Discriminant Analysis

**Version** 0.2

**Date** 2018-08-02

**Maintainer** Aaron J. Molstad <amolstad@fredhutch.org>

**Description** Fits the penalized matrix-normal model to be used for linear discriminant analysis with matrix-valued predictors. For a description of the method, see Molstad and Rothman (2018) <[doi:10.1080/10618600.2018.1476249](https://doi.org/10.1080/10618600.2018.1476249)>.

**License** GPL-2

**URL** [ajmolstad@github.io](mailto:ajmolstad@github.io)

**LazyData** TRUE

**Imports** Rcpp (>= 0.12.1), plyr, glasso

**LinkingTo** Rcpp, RcppArmadillo

**RoxygenNote** 5.0.1

**NeedsCompilation** yes

**Author** Aaron J. Molstad [aut, cre]

**Repository** CRAN

**Date/Publication** 2018-08-06 21:00:06 UTC

## Contents

MatLDA . . . . .	2
MatLDA_Grid . . . . .	5
MN_MLE . . . . .	8
PredictMN . . . . .	10
<b>Index</b>	<b>13</b>

---

MatLDA	<i>Fits the <math>J</math>-class penalized matrix-normal model for a single pair of tuning parameters.</i>
--------	--

---

### Description

A function for fitting the  $J$ -class penalized matrix-normal model based on a single set of tuning parameters  $(\lambda_1, \lambda_2)$ . Returns an object of class "MN", which can be used for prediction using the PredictMN function.

### Usage

```
MatLDA(X, class, lambda1, lambda2, quiet = TRUE, Xval = NULL,
       classval = NULL, k.iter = 100, cov.tol = 1e-05, m.tol = 1e-05,
       full.tol = 1e-06)
```

### Arguments

X	An $r \times c \times N$ array of training set predictors.
class	$N$ -vector of training set class labels; should be numeric from $\{1, \dots, J\}$ .
lambda1	A non-negative tuning parameter for the mean penalty.
lambda2	A non-negative tuning parameter for the Kronecker penalty.
quiet	Logical. Should the objective function value be printed at each update? Default is TRUE. Note that quiet=FALSE will increase computational time.
Xval	An $r \times c \times N_{\text{val}}$ array of validation set predictors. Default is NULL.
classval	$N_{\text{val}}$ -vector of validation set class labels; should be numeric from $\{1, \dots, J\}$ . Default is NULL.
k.iter	Maximum number of iterations for full blockwise coordinate descent algorithm.
cov.tol	Convergence tolerance for graphical lasso sub-algorithms; passed to glasso. Default is $1e^{-5}$ .
m.tol	Convergence tolerance for mean update alternating minimization algorithm. Default is $1e^{-5}$ . It is recommended to track the objective function value using quiet = FALSE and adjust if necessary.
full.tol	Convergence tolerance for full blockwise coordinate descent algorithm; based on decrease in objective function value. Default is $1e^{-6}$ . It is recommended to track the objective function value using quiet = FALSE and adjust if necessary.

### Value

Returns of list of class "MN", which contains the following elements:

Val	The misclassification rate on the validation set, if provided.
Mean	$\hat{M}$ ; an $r \times c \times J$ array of estimated class means.
U	$\hat{U}$ ; the $r \times r$ estimated precision matrix for the row variables.
V	$\hat{V}$ ; the $c \times c$ estimated precision matrix for the column variables.
pi.list	$\hat{\pi}$ ; $J$ -vector with marginal class probabilities from training set.

## References

- Molstad, A. J., and Rothman, A. J. (2018). A penalized likelihood method for classification with matrix-valued predictors. *Journal of Computational and Graphical Statistics*.

## Examples

```
## Generate realizations of matrix-normal random variables
## set sample size, dimensionality, number of classes,
## and marginal class probabilities

N = 75
N.test = 150
N.val = 75

N.total = N + N.test + N.val

r = 16
p = 16
C = 3

pi.list = rep(1/C, C)

## create class means
M.array = array(0, dim=c(r, p, C))
M.array[3:4, 3:4, 1] = 1
M.array[5:6, 5:6, 2] = .5
M.array[3:4, 3:4, 3] = -2
M.array[5:6, 5:6, 3] = -.5

## create covariance matrices U and V
Uinv = matrix(0, nrow=r, ncol=r)
for (i in 1:r) {
  for (j in 1:r) {
    Uinv[i,j] = .5^abs(i-j)
  }
}

eoU = eigen(Uinv)
Uinv.sqrt = tcrossprod(tcrossprod(eoU$vec,
diag(eoU$val^(1/2))),eoU$vec)

Vinv = matrix(.5, nrow=p, ncol=p)
diag(Vinv) = 1
eoV = eigen(Vinv)
Vinv.sqrt = tcrossprod(tcrossprod(eoV$vec,
diag(eoV$val^(1/2))),eoV$vec)

## generate N.total realizations of matrix-variate normal data
set.seed(10)
dat.array = array(0, dim=c(r,p,N.total))
class.total = numeric(length=N.total)
```

```

for(jj in 1:N.total){
  class.total[jj] = sample(1:C, 1, prob=pi.list)
  dat.array[, ,jj] = tcrossprod(crossprod(Uinv.sqrt,
matrix(rnorm(r*p), nrow=r)),
Vinv.sqrt) + M.array[, ,class.total[jj]]
}

## store generated data
X = dat.array[, ,1:N]
X.val = dat.array[, ,(N+1):(N+N.val)]
X.test = dat.array[, ,(N+N.val+1):N.total]

class = class.total[1:N]
class.val = class.total[(N+1):(N+N.val)]
class.test = class.total[(N+N.val+1):N.total]

## fit two-dimensional grid of tuning parameters;
## measure classification accuracy on validation set
lambda1 = c(2^seq(-5, 0, by=1))
lambda2 = c(2^seq(-8, -4, by=1))
fit.grid = MatLDA_Grid(X=X, class=class, lambda1=lambda1,
lambda2=lambda2, quiet=TRUE,
Xval=X.val, classval= class.val,
k.iter = 100, cov.tol=1e-5, m.tol=1e-5, full.tol=1e-6)

## identify minimum misclassification proportion;
## select tuning parameters corresponding to
## smallest model at minimum misclassification proportion
CV.mat = fit.grid$Val.mat
G.mat = fit.grid$G.mat*(CV.mat==min(CV.mat))
ind1 = (which(G.mat==max(G.mat), arr.ind=TRUE))[,2]
ind2 = (which(G.mat==max(G.mat), arr.ind=TRUE))[,1]
out = unique(ind2[which(ind2==max(ind2))])
lambda1.cv = lambda1[out]
out2 = unique(max(ind1[ind2==out]))
lambda2.cv = lambda2[out2]

## refit model with single tuning parameter pair
out = MatLDA(X=X, class=class, lambda1=lambda1.cv,
lambda2=lambda2.cv, quiet=FALSE,
Xval=X.test, classval= class.test,
k.iter = 100, cov.tol=1e-5, m.tol=1e-5, full.tol=1e-6)

## print misclassification proportion on test set
out$Val

## print images of estimated mean differences
dev.new(width=10, height=3)
par(mfrow=c(1,3))
image(t(abs(out$M[, ,1] - out$M[, ,2]))[,r:1],
main=expression(paste("|", hat(mu)[1], "-", hat(mu)[2], "|")),
col = grey(seq(1, 0, length = 100)))
image(t(abs(out$M[, ,1] - out$M[, ,3]))[,r:1],

```

```

main=expression(paste("|", hat(mu)[1], "-", hat(mu)[3], "|")),
  col = grey(seq(1, 0, length = 100))
image(t(abs(out$M[,2] - out$M[,3]))[,r:1],
main=expression(paste("|", hat(mu)[2], "-", hat(mu)[3], "|")),
  col = grey(seq(1, 0, length = 100))

```

---

MatLDA_Grid	<i>Fits the J-class penalized matrix-normal model for a two-dimensional grid of tuning parameters. Used for tuning parameter selection.</i>
-------------	---

---

### Description

A function for fitting the penalized matrix normal model for a two-dimensional grid of tuning parameters. Meant to be used with a validation set to select tuning parameters. Can also be used inside a  $k$ -fold cross-validation function where the training set is the data outside the  $k$ th fold and the validation set is comprised of the  $k$ th fold sample data.

### Usage

```

MatLDA_Grid(X, class, lambda1, lambda2, quiet = TRUE, Xval = NULL,
  classval = NULL, k.iter = 100, cov.tol = 1e-05, m.tol = 1e-05,
  full.tol = 1e-06)

```

### Arguments

X	An $r \times c \times N$ array of training set predictors.
class	$N$ -vector of training set class labels; should be numeric from $\{1, \dots, J\}$ .
lambda1	A vector of non-negative candidate tuning parameters for the mean penalty.
lambda2	A vector of non-negative candidate tuning parameters for the Kronecker penalty.
quiet	Logical. Should the objective function value be printed at each update? Default is TRUE. Note that quiet=FALSE will increase computational time.
Xval	An $r \times c \times N_{\text{val}}$ array of validation set predictors. Default is NULL.
classval	$N_{\text{val}}$ -vector of validation set class labels; should be numeric from $\{1, \dots, J\}$ . Default is NULL.
k.iter	Maximum number of iterations for full blockwise coordinate descent algorithm. Default is 100.
cov.tol	Convergence tolerance for graphical lasso subalgorithms; passed to glasso. Default is $1e^{-5}$ .
m.tol	Convergence tolerance for mean update alternating minimization algorithm. Default is $1e^{-5}$ . It is recommended to track the objective function value using quiet = FALSE and adjust tolerance if necessary.
full.tol	Convergence tolerance for full blockwise coordinate descent algorithm; based on decrease in objective function value. Default is $1e^{-6}$ . It is recommended to track the objective function value using quiet = FALSE and adjust tolerance if necessary.

**Value**

Val.mat	A matrix of dimension $\text{length}(\lambda_1) \times \text{length}(\lambda_2)$ with validation set misclassification proportions.
G.mat	A matrix of dimension $\text{length}(\lambda_1) \times \text{length}(\lambda_2)$ with the number of pairwise mean differences that are zero, i.e., a larger entry corresponds to a more sparse model.
U.mat	A matrix of dimension $\text{length}(\lambda_1) \times \text{length}(\lambda_2)$ with the number of zeros in $\hat{U}$ .
V.mat	A matrix of dimension $\text{length}(\lambda_1) \times \text{length}(\lambda_2)$ with the number of zeros in $\hat{V}$ .

**References**

- Molstad, A. J., and Rothman, A. J. (2018). A penalized likelihood method for classification with matrix-valued predictors. *Journal of Computational and Graphical Statistics*.

**Examples**

```
## Generate realizations of matrix-normal random variables
## set sample size, dimensionality, number of classes,
## and marginal class probabilities

N = 75
N.test = 150
N.val = 75

N.total = N + N.test + N.val

r = 16
p = 16
C = 3

pi.list = rep(1/C, C)

## create class means
M.array = array(0, dim=c(r, p, C))
M.array[3:4, 3:4, 1] = 1
M.array[5:6, 5:6, 2] = .5
M.array[3:4, 3:4, 3] = -2
M.array[5:6, 5:6, 3] = -.5

## create covariance matrices U and V
Uinv = matrix(0, nrow=r, ncol=r)
for (i in 1:r) {
  for (j in 1:r) {
    Uinv[i,j] = .5^abs(i-j)
  }
}
```

```

eoU = eigen(Uinv)
Uinv.sqrt = tcrossprod(tcrossprod(eoU$vec,
diag(eoU$val^(1/2))),eoU$vec)

Vinv = matrix(.5, nrow=p, ncol=p)
diag(Vinv) = 1
eoV = eigen(Vinv)
Vinv.sqrt = tcrossprod(tcrossprod(eoV$vec,
diag(eoV$val^(1/2))),eoV$vec)

## generate N.total realizations of matrix-variate normal data
set.seed(10)
dat.array = array(0, dim=c(r,p,N.total))
class.total = numeric(length=N.total)
for(jj in 1:N.total){
class.total[jj] = sample(1:C, 1, prob=pi.list)
dat.array[, ,jj] = tcrossprod(crossprod(Uinv.sqrt,
matrix(rnorm(r*p), nrow=r)),
Vinv.sqrt) + M.array[, ,class.total[jj]]
}

## store generated data
X = dat.array[, ,1:N]
X.val = dat.array[, ,(N+1):(N+N.val)]
X.test = dat.array[, ,(N+N.val+1):N.total]

class = class.total[1:N]
class.val = class.total[(N+1):(N+N.val)]
class.test = class.total[(N+N.val+1):N.total]

## fit two-dimensional grid of tuning parameters;
## measure classification accuracy on validation set
lambda1 = c(2^seq(-5, 0, by=1))
lambda2 = c(2^seq(-8, -4, by=1))
fit.grid = MatLDA_Grid(X=X, class=class, lambda1=lambda1,
lambda2=lambda2, quiet=TRUE,
Xval=X.val, classval= class.val,
k.iter = 100, cov.tol=1e-5, m.tol=1e-5, full.tol=1e-6)

## identify minimum misclassification proportion;
## select tuning parameters corresponding to
## smallest model at minimum misclassification proportion
CV.mat = fit.grid$Val.mat
G.mat = fit.grid$G.mat*(CV.mat==min(CV.mat))
ind1 = (which(G.mat==max(G.mat), arr.ind=TRUE))[,2]
ind2 = (which(G.mat==max(G.mat), arr.ind=TRUE))[,1]
out = unique(ind2[which(ind2==max(ind2))])
lambda1.cv = lambda1[out]
out2 = unique(max(ind1[ind2==out]))
lambda2.cv = lambda2[out2]

## refit model with single tuning parameter pair
out = MatLDA(X=X, class=class, lambda1=lambda1.cv,

```

```

lambda2=lambda2.cv, quiet=FALSE,
Xval=X.test, classval= class.test,
k.iter = 100, cov.tol=1e-5, m.tol=1e-5, full.tol=1e-6)

## print misclassification proportion on test set
out$Val

## print images of estimated mean differences
dev.new(width=10, height=3)
par(mfrow=c(1,3))
image(t(abs(out$M[,1] - out$M[,2]))[,r:1],
main=expression(paste("|", hat(mu)[1], "-", hat(mu)[2], "|")),
col = grey(seq(1, 0, length = 100)))
image(t(abs(out$M[,1] - out$M[,3]))[,r:1],
main=expression(paste("|", hat(mu)[1], "-", hat(mu)[3], "|")),
col = grey(seq(1, 0, length = 100)))
image(t(abs(out$M[,2] - out$M[,3]))[,r:1],
main=expression(paste("|", hat(mu)[2], "-", hat(mu)[3], "|")),
col = grey(seq(1, 0, length = 100)))

```

---

MN\_MLE

---

*Matrix-normal maximum likelihood estimator*


---

### Description

A function for fitting the  $J$ -class matrix-normal model using maximum likelihood. Uses the so-called “flip-flop” algorithm after initializing at  $U = I_r$ .

### Usage

```
MN_MLE(X, class, max.iter = 1000, tol = 1e-06, quiet = TRUE)
```

### Arguments

<code>X</code>	An $r \times c \times N$ array of training set predictors.
<code>class</code>	$N$ -vector of training set class labels; should be numeric from $\{1, \dots, J\}$ .
<code>max.iter</code>	Maximum number of iterations for “flip-flop” algorithm.
<code>tol</code>	Convergence tolerance for the “flip flop” algorithm; based on decrease in negative log-likelihood.
<code>quiet</code>	Logical. Should the objective function value be printed at each update? Default is TRUE. Note that <code>quiet=FALSE</code> will increase computational time.



**Value**

Returns of list of class "MN", which contains the following elements:

Mean	$\bar{X}$ ; An $r \times c \times C$ array of sample class means.
U	$\hat{U}^{\text{MLE}}$ ; the $r \times r$ estimated precision matrix for the row variables.
V	$\hat{V}^{\text{MLE}}$ ; the $c \times c$ estimated precision matrix for the column variables.
pi.list	$\hat{\pi}$ ; $J$ -vector with marginal class probabilities from training set.

**References**

- Molstad, A. J., and Rothman, A. J. (2018). A penalized likelihood method for classification with matrix-valued predictors. *Journal of Computational and Graphical Statistics*.

**Examples**

```
## Generate realizations of matrix-normal random variables
## set sample size, dimensionality, number of classes,
## and marginal class probabilities

N = 75
N.test = 150

N.total = N + N.test

r = 16
p = 16
C = 3

pi.list = rep(1/C, C)

## create class means
M.array = array(0, dim=c(r, p, C))
M.array[3:4, 3:4, 1] = 1
M.array[5:6, 5:6, 2] = .5
M.array[3:4, 3:4, 3] = -2
M.array[5:6, 5:6, 3] = -.5

## create covariance matrices U and V
Uinv = matrix(0, nrow=r, ncol=r)
for (i in 1:r) {
  for (j in 1:r) {
    Uinv[i,j] = .5^abs(i-j)
  }
}

eoU = eigen(Uinv)
Uinv.sqrt = tcrossprod(tcrossprod(eoU$vec,
diag(eoU$val^(1/2))),eoU$vec)

Vinv = matrix(.5, nrow=p, ncol=p)
```

```

diag(Vinv) = 1
eoV = eigen(Vinv)
Vinv.sqrt = tcrossprod(tcrossprod(eoV$vec,
diag(eoV$val^(1/2))),eoV$vec)

## generate N.total realizations of matrix-variate normal data
set.seed(1)
X = array(0, dim=c(r,p,N.total))
class = numeric(length=N.total)
for(jj in 1:N.total){
class[jj] = sample(1:C, 1, prob=pi.list)
X[, ,jj] = tcrossprod(crossprod(Uinv.sqrt,
matrix(rnorm(r*p), nrow=r),
Vinv.sqrt) + M.array[, ,class[jj]])
}

## fit matrix-normal model using maximum likelihood
out = MN_MLE(X = X, class = class)

```

---

PredictMN

*Classify matrix-valued data based on a matrix-normal linear discriminant; an object of class "MN".*


---

### Description

A function for prediction based on an object of class "MN"; models fit by MatLDA or MN\_MLE.

### Usage

```
PredictMN(object, newdata, newclass = NULL)
```

### Arguments

object	An object of class "MN"; output from MatLDA or MN_MLE.
newdata	New data to be classified; an $r \times c \times N_{\text{test}}$ array.
newclass	Class labels for new data; should be <i>in</i> $\{1, \dots, J\}$ . Default is NULL.

### Value

pred.class	An $N_{\text{test}}$ -vector of predicted class membership based on the inputted object.
misclass	If newclass is non-NULL, returns the misclassification proportion on the test data set.
prob.mat	A $N_{\text{test}} \times J$ matrix with the value of discriminant evaluated at each test data point.

### References

- Molstad, A. J., and Rothman, A. J. (2018). A penalized likelihood method for classification with matrix-valued predictors. *Journal of Computational and Graphical Statistics*.

**Examples**

```

## Generate realizations of matrix-normal random variables
## set sample size, dimensionality, number of classes,
## and marginal class probabilities

N = 75
N.test = 150

N.total = N + N.test

r = 16
p = 16
C = 3

pi.list = rep(1/C, C)

## create class means
M.array = array(0, dim=c(r, p, C))
M.array[3:4, 3:4, 1] = 1
M.array[5:6, 5:6, 2] = .5
M.array[3:4, 3:4, 3] = -2
M.array[5:6, 5:6, 3] = -.5

## create covariance matrices U and V
Uinv = matrix(0, nrow=r, ncol=r)
for (i in 1:r) {
  for (j in 1:r) {
    Uinv[i,j] = .5^abs(i-j)
  }
}

eoU = eigen(Uinv)
Uinv.sqrt = tcrossprod(tcrossprod(eoU$vec, diag(eoU$val^(1/2))),eoU$vec)

Vinv = matrix(.5, nrow=p, ncol=p)
diag(Vinv) = 1
eoV = eigen(Vinv)
Vinv.sqrt = tcrossprod(tcrossprod(eoV$vec, diag(eoV$val^(1/2))),eoV$vec)

## generate N.total realizations of matrix-variate normal data
set.seed(1)
dat.array = array(0, dim=c(r,p,N.total))
class.total = numeric(length=N.total)
for(jj in 1:N.total){
  class.total[jj] = sample(1:C, 1, prob=pi.list)
  dat.array[,,jj] = tcrossprod(crossprod(Uinv.sqrt, matrix(rnorm(r*p), nrow=r)),
  Vinv.sqrt) + M.array[,,class.total[jj]]
}

## store generated data

```

```
X = dat.array[,1:N]
X.test = dat.array[, (N+1):N.total]

class = class.total[1:N]
class.test = class.total[(N+1):N.total]

## fit matrix-normal model using maximum likelihood
out = MN_MLE(X = X, class = class)

## use output to classify test set
check = PredictMN(out, newdata = X.test, newclass = class.test)

## print misclassification proportion
check$misclass
```

# Index

MatLDA, [2](#)  
MatLDA\_Grid, [5](#)  
MN\_MLE, [8](#)  
  
PredictMN, [10](#)