Package 'dina'

October 28, 2026

Type Package

Title Bayesian Estimation of DINA Model

Version 2.0.3

Description Estimate the Deterministic Input, Noisy ``And'' Gate (DINA) cognitive diagnostic model parameters using the Gibbs sampler described by Culpepper (2015) <doi:10.3102/1076998615595403>.

URL https://github.com/tmsalab/dina, https://tmsalab.github.io/dina/

BugReports https://github.com/tmsalab/dina/issues

License GPL (>= 2)

Depends R (>= 4.3.0), simcdm (>= 0.1.0)

Imports Rcpp (>= 1.1.0)

LinkingTo Rcpp, RcppArmadillo (>= 15.0.2-2), simcdm, rgen

Suggests CDM, covr, testthat

RoxygenNote 7.3.3

Encoding UTF-8

NeedsCompilation yes

Author Steven Andrew Culpepper [aut, cph] (ORCID: <https://orcid.org/0000-0003-4226-6176>), James Joseph Balamuta [aut, cre] (ORCID: <https://orcid.org/0000-0003-2826-8458>)

Maintainer James Joseph Balamuta <balamut2@illinois.edu>

Repository CRAN

Date/Publication 2026-10-28 13:50:10 UTC

Contents

dina-package 2
dina 2
DINA_Gibbs 5

Index **7**

dina-package *dina: Bayesian Estimation of DINA Model*

Description

Estimate the Deterministic Input, Noisy "And" Gate (DINA) cognitive diagnostic model parameters using the Gibbs sampler described by Culpepper (2015) doi:10.3102/1076998615595403.

Author(s)

Maintainer: James Joseph Balamuta <balamut2@illinois.edu> (ORCID)

Authors:

- Steven Andrew Culpepper <sculpepp@illinois.edu> (ORCID) [copyright holder]

See Also

Useful links:

- https://github.com/tmsalab/dina
- https://tmsalab.github.io/dina/
- Report bugs at https://github.com/tmsalab/dina/issues

dina *Generate Posterior Distribution with Gibbs sampler*

Description

Function for sampling parameters from full conditional distributions. The function returns a list of arrays or matrices with parameter posterior samples. Note that the output includes the posterior samples in objects.

Usage

```
dina(Y, Q, chain_length = 10000)
```

Arguments

Y	A $N \times J$ matrix of observed responses.
Q	A $N \times K$ matrix indicating which skills are required for which items.
chain_length	Number of MCMC iterations.

Value

A `list` with samples from the posterior distribution with each entry named:

- `CLASSES` = individual attribute profiles,
- `PIs` = latent class proportions,
- `SigS` = item slipping parameters, and
- `GamS` = item guessing parameters.

Author(s)

Steven Andrew Culpepper and James Joseph Balamuta

See Also

`simcdm::sim_dina_items()` and `simcdm::attribute_classes()`

Examples

```
## Not run:

###################################
# Tatsuoka Fraction Subtraction Data
###################################

# This example requires data from the CDM package.
if(requireNamespace("CDM")) {

data(fraction.subtraction.data, package = "CDM")
data(fraction.subtraction.qmatrix, package = "CDM")
Y_1984 = as.matrix(fraction.subtraction.data)
Q_1984 = as.matrix(fraction.subtraction.qmatrix)
K_1984 = ncol(fraction.subtraction.qmatrix)
J_1984 = ncol(Y_1984)

# Creating matrix of possible attribute profiles
As_1984 = rep(0, K_1984)

for(j in 1:K_1984) {
    temp = combn(1:K_1984, m = j)
    tempmat = matrix(0, ncol(temp), K_1984)
    for(j in 1:ncol(temp)) tempmat[j, temp[, j]] = 1
    As_1984 = rbind(As_1984, tempmat)
}

As_1984 = as.matrix(As_1984)

# Generate samples from posterior distribution
# May take 8 minutes
chainLength = 5000
burnin = 1000
chain_samples = burnin:chainLength
```

```
outchain_1984 = dina(Y = Y_1984, Q = Q_1984,
                     chain_length = chainLength)

# Summarize posterior samples for g and 1-s
mgs_1984 = apply(outchain_1984$GamS[, chain_samples], 1, mean)
sgs_1984 = apply(outchain_1984$GamS[, chain_samples], 1, sd)
mss_1984 = 1 - apply(outchain_1984$SigS[, chain_samples], 1, mean)
sss_1984 = apply(outchain_1984$SigS[, chain_samples], 1, sd)
output_1984 = cbind(mgs_1984, sgs_1984, mss_1984, sss_1984)
colnames(output_1984) = c('g Est','g SE','1-s Est','1-s SE')
rownames(output_1984) = colnames(Y_1984)
print(output_1984, digits = 3)

# Summarize marginal skill distribution using posterior samples for latent
# class proportions
marg_PIs = t(As_1984) %*% outchain_1984$PIs
PI_Est = apply(marg_PIs[, chain_samples], 1, mean)
PI_Sd = apply(marg_PIs[, chain_samples], 1, sd)
PIoutput = cbind(PI_Est, PI_Sd)
colnames(PIoutput) = c('EST', 'SE')
rownames(PIoutput) = paste('Skill', 1:K_1984)
print(PIoutput, digits = 3)

}

#########################################################
# de la Torre (2009) Simulation Replication w/ N = 200
#########################################################
N = 200
K = 5
J = 30
delta0 = rep(1, 2^K)

# Creating Q matrix
Q = matrix(rep(diag(K), 2), 2*K, K, byrow = TRUE)

for(mm in 2:K) {
    temp = combn(1:K, m = mm)
    tempmat = matrix(0, ncol(temp), K)
    for(j in 1:ncol(temp)) tempmat[j, temp[, j]] = 1
    Q = rbind(Q, tempmat)
}

Q = Q[1:J,]

# Setting item parameters and generating attribute profiles
ss = gs = rep(.2, J)
PIs = rep(1/(2^K), 2^K)
CLs = c(1:(2^K)) %*% rmultinom(n = N, size = 1, prob = PIs)

# Defining matrix of possible attribute profiles
As = rep(0,K)
```

```
for(j in 1:K) {
    temp = combn(1:K, m = j)
    tempmat = matrix(0, ncol(temp), K)
    for(j in 1:ncol(temp)) tempmat[j, temp[, j]] = 1
    As = rbind(As, tempmat)
}

As = as.matrix(As)

# Sample true attribute profiles
Alphas = As[CLs,]

# Simulate data under DINA model
Y_sim = simcdm::sim_dina_items(Alphas, Q, ss, gs)

## Execute MCMC DINA routine ----

# NOTE: This example uses a small chain length to reduce
# computation time to illustrate the pedagogical concept.
# In a real-life scenario, increase the chain length to
# at least 5,000.

chainLength = 200
burnin = 100

outchain = dina(Y_sim, Q, chain_length = chainLength)

## Summarize posterior samples for g and 1-s ----

chain_samples = burnin:chainLength
mGs = apply(outchain$GamS[, chain_samples], 1, mean)
sGs = apply(outchain$GamS[, chain_samples], 1, sd)
m1mSS = 1 - apply(outchain$SigS[, chain_samples], 1, mean)
s1mSS = apply(outchain$SigS[, chain_samples], 1, sd)
output = cbind(mGs, sGs, m1mSS, s1mSS)
colnames(output) = c('g Est', 'g SE', '1-s Est', '1-s SE')
rownames(output) = paste('Item', 1:J)
print(output, digits = 3)

## Summarize marginal skill distribution ----

# Via posterior samples for latent class proportions
PIoutput = cbind(apply(outchain$PIs, 1, mean), apply(outchain$PIs, 1, sd))
colnames(PIoutput) = c('EST', 'SE')
rownames(PIoutput) = apply(As, 1, paste0, collapse='')
print(PIoutput, digits = 3)

## End(Not run)
```

DINA_Gibbs *Deprecated functions*

Description

Functions found within this help documentation have been deprecated.

Usage

```
DINA_Gibbs(...)
```

Arguments

...	Old parameters

Details

Deprecated functions

- `DINA_Gibbs` in favor of `dina`

Index

dina, 2
dina-package, 2
DINA_Gibbs, 5

simcdm::attribute_classes(), *3*
simcdm::sim_dina_items(), *3*