

Package ‘smog’

October 14, 2022

Type Package

Title Structural Modeling by using Overlapped Group Penalty

Version 2.1.0

Date 2020-08-01

Maintainer Chong Ma <chongma8903@gmail.com>

Description Fits a linear non-penalized phenotype (demographic) variables and penalized groups of prognostic effect and predictive effect, by satisfying such hierarchy structures that if a predictive effect exists, its prognostic effect must also exist. This package can deal with continuous, binomial or multinomial, and survival response variables, underlying the assumption of Gaussian, binomial (multinomial), and Cox proportional hazard models, respectively. It is implemented by combining the iterative shrinkage-thresholding algorithm and the alternating direction method of multipliers algorithms. The main method is built in C++, and the complementary methods are written in R.

URL <https://github.com/chongma8903/smog>

BugReports <https://github.com/chongma8903/smog/issues>

Depends R (>= 3.6)

Imports Rcpp (>= 0.12.18), foreach, doParallel, dplyr, tidyr, magrittr, ggplot2, Rdpack, rmarkdown

Suggests survival, roxygen2, pkgdown

RdMacros Rdpack

License GPL (>= 2)

Encoding UTF-8

LazyData true

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 6.1.1

NeedsCompilation yes

Author Chong Ma [aut, cre],
Kevin Galinsky [ctb]

Repository CRAN

Date/Publication 2020-08-10 16:50:02 UTC

R topics documented:

glog	2
penalty	4
plot.cv.cglasso	5
plot.cv.smog	6
plot.smog	8
predict.smog	9
prox	10
proxL1	11
proxL2	11
sim_rct_biomarker	12
smog.default	14

Index	18
--------------	-----------

glog	<i>Generalized linear model constraint on hierarchical structure by using overlapped group penalty</i>
------	--

Description

Generalized linear model constraint on hierarchical structure by using overlapped group penalty

Usage

```
glog(y, x, g, v, lambda, hierarchy, family = "gaussian", rho = 10,
     scale = TRUE, eabs = 0.001, erel = 0.001, LL = 1, eta = 1.25,
     maxitr = 1000L)
```

Arguments

y	response variable, in the format of matrix. When family is 'gaussian' or 'binomial', y ought to be a matrix of n by 1 for the observations; when family is "coxph", y represents the survival objects, that is, a matrix of n by 2, containing the survival time and the censoring status. See Surv .
x	a model matrix of dimensions n by p, in which the column represents the predictor variables.
g	a numeric vector of group labels for the predictor variables.
v	a numeric vector of binary values, represents whether or not the predictor variables are penalized. Note that 1 indicates penalization and 0 for not penalization.
lambda	a numeric vector of three penalty parameters corresponding to L2 norm, squared L2 norm, and L1 norm, respectively.
hierarchy	a factor value in levels 0, 1, 2, which represent different hierarchical structure within groups, respectively. When hierarchy=0, λ_2 and λ_3 are forced to be zeroes; when hierarchy=1, λ_2 is forced to be zero; when hierarchy=2, there is no constraint on λ 's. See smog .

family	a description of the distribution family for the response variable variable. For continuous response variable, family is gaussian' '; for multinomial or binary response variable, family is binomial"; for survival response variable, family is "coxph", respectively.
rho	the penalty parameter used in the alternating direction method of multipliers algorithm (ADMM). Default is 10.
scale	whether or not scale the design matrix. Default is true.
eabs	the absolute tolerance used in the ADMM algorithm. Default is 1e-3.
erel	the relative tolerance used in the ADMM algorithm. Default is 1e-3.
LL	initial value for the Lipschitz continuous constant for approximation to the objective function in the Majorization- Minimization (MM) (or iterative shrinkage-thresholding algorithm (ISTA)). Default is 1.
eta	gradient stepsize for the backtrack line search for the Lipschitz continuous constant. Default is 1.25.
maxitr	the maximum iterations for convergence in the ADMM algorithm. Default is 500.

Value

A list of

coefficients	A data frame of the variable name and the estimated coefficients
llikelihood	The log likelihood value based on the ultimate estimated coefficients
loglike	The sequence of log likelihood values since the algorithm starts
PrimalError	The sequence of primal errors in the ADMM algorithm
DualError	The sequence of dual errors in the ADMM algorithm
converge	The integer of the iteration when the convergence occurs

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

[cv.smog](#), [smog.default](#), [smog.formula](#), [predict.smog](#), [plot.smog](#).

Examples

```

set.seed(2018)
# generate design matrix x
n=50;p=100
s=10
x=matrix(0,n,1+2*p)
x[,1]=sample(c(0,1),n,replace = TRUE)
x[,seq(2,1+2*p,2)]=matrix(rnorm(n*p),n,p)
x[,seq(3,1+2*p,2)]=x[,seq(2,1+2*p,2)]*x[,1]

g=c(p+1,rep(1:p,rep(2,p))) # groups
v=c(0,rep(1,2*p))        # penalization status

# generate beta
beta=c(rnorm(13,0,2),rep(0,ncol(x)-13))
beta[c(2,4,7,9)]=0

# generate y
data1=x%*%beta
noise1=rnorm(n)
snr1=as.numeric(sqrt(var(data1)/(s*var(noise1))))
y1=data1+snr1*noise1
lambda = c(8,0,8)
hierarchy = 1
gfit1 = glog(y1,x,g,v,lambda,hierarchy,family = "gaussian")

```

penalty

Penalty function on the composite L2, L2-Square, and L1 penalties

Description

Penalty function on the composite L2, L2-Square, and L1 penalties

Usage

```
penalty(x, lambda, hierarchy, d)
```

Arguments

x	A vector of two numeric values, in which x_1 represents the prognostic effect, and x_2 for the predictive effect, respectively.
lambda	a vector of three penalty parameters. λ_1 and λ_2 are L2 and L2-Square (ridge) penalties for x in a group level, and λ_3 is the L1 penalty for x_2 , respectively.
hierarchy	a factor value in levels 0, 1, 2, which represent different hierarchical structure in x , respectively. When $\text{hierarchy}=0$, λ_2 and λ_3 are forced to be zeroes; when $\text{hierarchy}=1$, λ_2 is forced to be zero; when $\text{hierarchy}=2$, there is no constraint on λ 's. See smog .
d	indices for overlapped variables in x .

Value

A numeric value of the penalty function based on the composition of L2, L2-Square, and L2 penalties.

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

[cv.smog](#), [smog.default](#), [smog.formula](#), [predict.smog](#), [plot.smog](#).

Examples

```
penalty(x = rnorm(6,2,1), lambda = c(0.5,0.3,0.1), hierarchy = 0, d = c(1,1,2,2,3,3))
```

plot.cv.cglasso *plot method for objects of cv.cglasso class*

Description

Yields a cross-validation curve, and error bars within one standard deviation of the curve, as a function of the group penalty λ_1 .

Usage

```
## S3 method for class 'cv.cglasso'  
plot(x, ...)
```

Arguments

x	An fitted object in "cv.cglasso" class.
...	Other graphical parameters to ggplot2.

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

[cv.cglasso](#), [cv.smog](#), [smog](#).

Examples

```
# generate design matrix x
set.seed(2018)
n=50;p=20
s=10
x=matrix(0,n,1+2*p)
x[,1]=sample(c(0,1),n,replace = TRUE)
x[,seq(2,1+2*p,2)]=matrix(rnorm(n*p),n,p)
x[,seq(3,1+2*p,2)]=x[,seq(2,1+2*p,2)]*x[,1]

g=c(p+1,rep(1:p,rep(2,p))) # groups
v=c(0,rep(1,2*p)) # penalization status
label=c("t",rep(c("prog","pred"),p)) # type of predictor variables

# generate beta
beta=c(rnorm(13,0,2),rep(0,ncol(x)-13))
beta[c(2,4,7,9)]=0

# generate y
data=x%*%beta
noise=rnorm(n)
snr=as.numeric(sqrt(var(data)/(s*var(noise))))
y=data+snr*noise

cvfit=cv.cglasso(x,y,g,v,label,family="gaussian", nlambda.max = 20)
plot(cvfit)
```

plot.cv.smog

plot method for objects of cv.smog class

Description

Yield a search path for optimal group penalty $G - \lambda$ and $I - \lambda$ using the mean-squared errors from the cross-validations.

Usage

```
## S3 method for class 'cv.smog'
plot(x, ...)
```

Arguments

`x` An fitted object in "cv.smog" class.
`...` Other graphical parameters to ggplot2.

Details

x-axis represents the group tuning parameter λ_G and y-axis for the interaction tuning parameter λ_I , respectively. The point size demonstrates the magnitude of MSE or negative log-likelihood.

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

[smog](#), [cv.smog](#), [cv.cglasso](#).

Examples

```
# generate design matrix x
set.seed(2018)
n=100;p=20
s=10
x=matrix(0,n,1+2*p)
x[,1]=sample(c(0,1),n,replace = TRUE)
x[,seq(2,1+2*p,2)]=matrix(rnorm(n*p),n,p)
x[,seq(3,1+2*p,2)]=x[,seq(2,1+2*p,2)]*x[,1]

g=c(p+1,rep(1:p,rep(2,p))) # groups
v=c(0,rep(1,2*p))        # penalization status
label=c("t",rep(c("prog","pred"),p)) # type of predictor variables

# generate beta
beta=c(rnorm(13,0,2),rep(0,ncol(x)-13))
beta[c(2,4,7,9)]=0

# generate y
data=x%*%beta
noise=rnorm(n)
snr=as.numeric(sqrt(var(data)/(s*var(noise))))
y=data+snr*noise

cvfit=cv.smog(x,y,g,v,label,type = "AIC", family="gaussian")
plot(cvfit)
```

`plot.smog`*plot method for objects of smog class*

Description

`plot.smog` can produce a panel of plots for the primal errors, dual errors, and the penalized log-likelihood values, based on the provided fitted model (`x`) in the S3method of `smog`.

Usage

```
## S3 method for class 'smog'  
plot(x, type = "l", xlab = "iteration",  
      caption = list("primal error", "dual error", "log-likelihood"), ...)
```

Arguments

<code>x</code>	a fitted object of class inheriting from <code>smog</code> .
<code>type</code> , <code>xlab</code>	default line types and x axis labels for the panel of plots.
<code>caption</code>	a list of y axes labels for the panel of plots.
<code>...</code>	additional arguments that could be supplied to <code>plot.default</code> and <code>par</code> .

Details

For the panel of three plots, the `xlab` is "iterations" and the `type` is "l", by default. The `ylab` are "primal error", "dual error", "log-likelihood", respectively. This panel of plots can reflect the convergence performance for the algorithm used in `smog`.

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

`par`, `plot.default`, `predict.smog`, `smog.default`, `cv.smog`.

predict.smog	<i>predict method for objects of the class smog</i>
--------------	---

Description

predict.smog can produce the prediction for user-given new data, based on the provided fitted model (object) in the S3method of smog. If the newdata omitted, it would output the prediction for the fitted model itself. The yielded result should match with the family in the provided model. See [smog](#).

Usage

```
## S3 method for class 'smog'  
predict(object, newdata = NULL, family = "gaussian",  
        ...)
```

Arguments

object	a fitted object of class inheriting from smog.
newdata	a data frame containing the predictor variables, which are used to predict. If omitted, the fitted linear predictors are used.
family	a description of distribution family for which the response variable is to be predicted.
...	additional arguments affecting the predictions produced.

Details

If newdata = NULL, the fitted.value based on the object is used for the prediction. For family = "coxph", the returned prediction value is the risk score.

Value

If family = "gaussian", a vector of prediction for the response is returned. For family = "coxph", a vector of predicted risk score is returned. When family = "binomial", it outputs a data frame containing the predicted group labels and the corresponding probabilities.

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

[smog.default](#), [smog.formula](#), [cv.smog](#), [plot.smog](#).

prox	<i>Composite proximal operator based on L2, L2-Square, and L1 penalties</i>
------	---

Description

Composite proximal operator based on L2, L2-Square, and L1 penalties

Usage

```
prox(x, lambda, hierarchy, d)
```

Arguments

x	A numeric vector of two.
lambda	a vector of three penalty parameters. λ_1 and λ_2 are L2 and L2-Square (ridge) penalties for x in a group level, and λ_3 is the L1 penalty for x_2 , respectively.
hierarchy	a factor value in levels 0, 1, 2, which represent different hierarchical structure in x , respectively. When <code>hierarchy=0</code> , λ_2 and λ_3 are forced to be zeroes; when <code>hierarchy=1</code> , λ_2 is forced to be zero; when <code>hierarchy=2</code> , there is no constraint on λ 's. See smog .
d	indices for overlapped variables in x .

Value

A two-dimensional numerical vector, soft-thresholded based on a composition of λ_1 , λ_2 , and λ_3 .

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

[cv.smog](#), [smog.default](#), [smog.formula](#), [predict.smog](#), [plot.smog](#).

Examples

```
prox(x = rnorm(6,2,1), lambda = c(0.5,0.3,0.1), hierarchy = 0, d = c(1,1,2,2,3,3))
```

proxL1	<i>L1 proximal operator</i>
--------	-----------------------------

Description

L1 proximal operator

Usage

proxL1(x, lambda)

Arguments

x	numeric value.
lambda	numeric value for the L1 penalty parameter.

Value

A numeric value soft-thresholded by λ , which is $sign(x)(|x| - \lambda)_+$.

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

Examples

proxL1(2.0, 0.5)

proxL2	<i>L2 proximal operator</i>
--------	-----------------------------

Description

L2 proximal operator

Usage

proxL2(x, lambda)

Arguments

`x` A vector of p numerical values.
`lambda` numeric value for the L2 penalty parameter.

Value

A numeric vector soft-thresholded by λ as a group, which is $(1 - \frac{\lambda\sqrt{p}}{\sqrt{x_1^2 + \dots + x_p^2}})_+ \mathbf{x}$.

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

Examples

```
proxL2(rnorm(6,2,1),0.5)
```

sim_rct_biomarker *Simulate a randomized clinical trial with biomarkers*

Description

`sim_rct_biomarker` is used to simulate clinical trial data with specified treatment, prognostic, and predictive effect sizes.

Usage

```
sim_rct_biomarker(n = 50, p = 100, p_prog = 5, p_pred = 5,
  p_both = 5, v_trt = 0.4, v_prog = 0.2, v_pred = 0.2,
  v_err = 0.2, corr = NULL, family = "gaussian", ...)
```

Arguments

`n` Number of subjects.
`p` Number of biomarkers.
`p_prog` Number of biomarkers with prognostic effects only.
`p_pred` Number of biomarkers with predictive effects only.
`p_both` Number of biomarkers with both prognostic and predictive effects
`v_trt` Variance of response due to treatment.
`v_prog` Variance of response due to prognostic effects.

v_pred	Variance of response due to predictive effects.
v_err	Variance of response due to random noise.
corr	Autocorrelation parameter between biomarkers, default is NULL.
family	The distribution family for response variable, can be gaussian', or binomial'. Default is "gaussian".
...	further arguments passed to or from other methods.

Value

A list containing several variables.

T Treatment status in 1 or -1 values.

X Biomarkers.

W Hadamard product of treatment and biomarkers.

M Model matrix - binding of T, X, and W.

Y Response.

Y0 Response without error.

tau Treatment effect.

beta Prognostic effects.

gamma Predictive effects.

theta All effects corresponding to M.

Author(s)

Chong Ma <chong.ma@yale.edu>, Kevin Galinsky <Kevin.Galinsky@takeda.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

Examples

```
sim <- sim_rct_biomarker(n = 1e3)
var(as.vector(sim$T * sim$tau))
var(as.vector(sim$X %*% sim$beta))
var(as.vector(sim$W %*% sim$gamma))
```

smog.default	<i>Generalized linear model constraint on hierarchical structure by using overlapped group penalty</i>
--------------	--

Description

smog fits a linear non-penalized phenotype (demographic) variables such as age, gender, treatment, etc, and penalized groups of prognostic effect (main effect) and predictive effect (interaction effect), by satisfying the hierarchy structure: if a predictive effect exists, its prognostic effect must be in the model. It can deal with continuous, binomial or multinomial, and survival response variables, underlying the assumption of Gaussian, binomial (multinomial), and Cox proportional hazard models, respectively. It can accept [formula](#), and output coefficients table, fitted.values, and convergence information produced in the algorithm iterations.

Usage

```
## Default S3 method:
smog(x, y, g, v, label, lambda1, lambda2, lambda3,
     family = "gaussian", subset = NULL, rho = 10, scale = TRUE,
     eabs = 0.001, erel = 0.001, LL = 1, eta = 1.25, maxitr = 1000,
     ...)

## S3 method for class 'formula'
smog(formula, data = list(), g, v, label, lambda1,
     lambda2, lambda3, ...)
```

Arguments

x	a model matrix, or a data frame of dimensions n by p, in which the columns represents the predictor variables.
y	response variable, corresponds to the family description. When family is "gaussian" or "binomial", y ought to be a numeric vector of observations of length n; when family is "coxph", y represents the survival objects, containing the survival time and the censoring status. See Surv .
g	a vector of group labels for the predictor variables.
v	a vector of binary values, represents whether or not the predictor variables are penalized. Note that 1 indicates penalization and 0 for not penalization.
label	a character vector, represents the type of predictors in terms of treatment, prognostic, and predictive effects by using "t", "prog", and "pred", respectively.
lambda1	penalty parameter for the L2 norm of each group of prognostic and predictive effects.
lambda2	ridge penalty parameter for the squared L2 norm of each group of prognostic and predictive effects.
lambda3	penalty parameter for the L1 norm of predictive effects.

family	a description of the distribution family for the response variable variable. For continuous response variable, family is "gaussian"; for multinomial or binary response variable, family is "binomial"; for survival response variable, family is "coxph", respectively.
subset	an optional vector specifying a subset of observations to be used in the model fitting. Default is NULL.
rho	the penalty parameter used in the alternating direction method of multipliers (ADMM) algorithm. Default is 10.
scale	whether or not scale the design matrix. Default is TRUE.
eabs	the absolute tolerance used in the ADMM algorithm. Default is 1e-3.
erel	the relative tolerance used in the ADMM algorithm. Default is 1e-3.
LL	initial value for the Lipschitz continuous constant for approximation to the objective function in the Majorization- Minimization (MM) (or iterative shrinkage-thresholding algorithm (ISTA)). Default is 1.
eta	gradient stepsize for the backtrack line search for the Lipschitz continuous constant. Default is 1.25.
maxitr	the maximum iterations for convergence in the ADMM algorithm. Default is 1000.
...	other relevant arguments that can be supplied to smog.
formula	an object of class "formula": a symbolic description of the model to be fitted. Should not include the intercept.
data	an optional data frame, containing the variables in the model.

Details

The formula has the form $\text{response} \sim \theta + \text{terms}$ where *terms* is a series of predictor variables to be fitted for response. For *gaussian* family, the response is a continuous vector. For *binomial* family, the response is a factor vector, in which the last level denotes the "pivot". For *coxph* family, the response is a [Surv](#) object, containing the survival time and censoring status.

Value

smog returns an object of class inhering from "smog". The generic accessor functions `coef`, `coefficients`, `fitted.value`, and `predict` can be used to extract various useful features of the value returned by smog. An object of "smog" is a list containing at least the following components:

:

coefficients Data frame containing the nonzero predictor variables' indexes, names, and estimates. When family is "binomial", the estimates have K-1 columns, each column representing the weights for the corresponding group. The last group behaves the "pivot".

fitted.values The fitted mean values for the response variable, for family is "gaussian". When family is "binomial", the fitted.values are the probabilities for each class; when family is "coxph", the fitted.values are risk scores.

residuals The residual is trivial for family = "gaussian". For family = "binomial", Pearson residuals is returned; and for family = "coxph", it yields deviance residuals, i.e., standardized martingale residuals.

model A list of estimates for the intercept, treatment effect, and prognostic and predictive effects for the selected biomarkers.

weight The weight of predictors resulted from the penalty function, is used to calculate the degrees of freedom.

DF the degrees of freedom. When family = "gaussian", $DF = tr(x'_\lambda(x'_\lambda x_\lambda + W)x_\lambda)$. For other families, DF is approximated by $diag(1/(1 + W))$.

criteria model selection criteria, including the correction Akaike's Information Criterion (AIC), AIC, Bayesian Information Criterion (BIC), and the generalized cross-validation score (GCV), respectively. See also [cv.smog](#).

likelihood the log-likelihood value for the converged model.

loglike the penalized log-likelihood values for each iteration in the algorithm.

PrimalError the averaged norms $\|\beta - Z\|/\sqrt{p}$ for each iteration, in the ADMM algorithm.

DualError the averaged norms $\|Z^{t+1} - Z^t\|/\sqrt{p}$ for each iteration, in the ADMM algorithm.

converge the number of iterations processed in the ADMM algorithm.

call the matched call.

formula the formula supplied.

Penalized regression model

The regression function contains the non-penalized predictor variables, and many groups of prognostic and predictive terms, where in each group the prognostic term comes first, followed by the predictive term.

- Penalty function: Different hierarchical structures within groups can result from adjusting the penalty parameters in the penalty function:

$$\Omega(\beta) = \lambda_1 \|\beta\| + \lambda_2 \|\beta\|^2 + \lambda_3 |\beta_2|$$

Where $\beta = (\beta_1, \beta_2)$. Note that β_1 denotes the prognostic effect (main effect), and β_2 for the predictive effect (interactive effect), respectively. When $\lambda_2 = 0$ and $\lambda_3 = 0$, it indicates no structure within groups. When $\lambda_2 \neq 0$, the penalty function honors the structure within groups such that: predictive effect $\neq 0 \implies$ prognostic effect $\neq 0$.

- Tuning parameters: rho, eabs, ere1, LL, eta are the corresponding parameters used in the iterative shrinkage-thresholding algorithm (ISTA) and the alternating direction method of multipliers algorithm (ADMM).

Author(s)

Chong Ma, <chongma8903@gmail.com>.

References

Ma C, Deng W, Ma S, Liu R, Galinsky K (2019). "Structural modeling using overlapped group penalties for discovering predictive biomarkers for subgroup analysis." *arXiv preprint arXiv:1904.11648*.

See Also

[cv.smog](#), [predict.smog](#), [plot.smog](#).

Examples

```

n=100;p=20
set.seed(2018)
# generate design matrix x
s=10
x=matrix(0,n,1+2*p)
x[,1]=sample(c(0,1),n,replace = TRUE)
x[,seq(2,1+2*p,2)]=matrix(rnorm(n*p),n,p)
x[,seq(3,1+2*p,2)]=x[,seq(2,1+2*p,2)]*x[,1]

g=c(p+1,rep(1:p,rep(2,p))) # groups
v=c(0,rep(1,2*p)) # penalization status
label=c("t",rep(c("prog","pred"),p)) # type of predictor variables

# generate beta
beta=c(rnorm(13,0,2),rep(0,ncol(x)-13))
beta[c(2,4,7,9)]=0

# generate y
data1=x%%beta
noise1=rnorm(n)
snr1=as.numeric(sqrt(var(data1)/(s*var(noise1))))
y1=data1+snr1*noise1
lfit1=smog(x,y1,g,v,label,lambda1=8,lambda2=0,lambda3=8,family = "gaussian")

## generate binomial data
prob=exp(as.matrix(x)%%as.matrix(beta))/(1+exp(as.matrix(x)%%as.matrix(beta)))
y2=ifelse(prob<0.5,0,1)
lfit2=smog(x,y2,g,v,label,lambda1=0.03,lambda2=0,lambda3=0.03,family = "binomial")

## generate survival data
# Weibull latent event times
lambda = 0.01; rho = 1
V = runif(n)
Tlat = (- log(V) / (lambda*exp(x %% beta)) )^(1/rho)
C = rexp(n, 0.001) ## censoring time
time = as.vector(pmin(Tlat, C))
status = as.numeric(Tlat <= C)
y3 = as.matrix(cbind(time = time, status = status))

lfit3=smog(x,y3,g,v,label,lambda1=0.2,lambda2=0,lambda3=0.2,family = "coxph")

```

Index

`cv.cglasso`, [6](#), [7](#)
`cv.smog`, [3](#), [5–10](#), [16](#)

`formula`, [14](#)

`glog`, [2](#)

`par`, [8](#)
`penalty`, [4](#)
`plot.cv.cglasso`, [5](#)
`plot.cv.smog`, [6](#)
`plot.default`, [8](#)
`plot.smog`, [3](#), [5](#), [8](#), [9](#), [10](#), [16](#)
`predict.smog`, [3](#), [5](#), [8](#), [9](#), [10](#), [16](#)
`prox`, [10](#)
`proxL1`, [11](#)
`proxL2`, [11](#)

`sim_rct_biomarker`, [12](#)
`smog`, [2](#), [4](#), [6–10](#)
`smog.default`, [3](#), [5](#), [8–10](#), [14](#)
`smog.formula`, [3](#), [5](#), [9](#), [10](#)
`smog.formula (smog.default)`, [14](#)
`Surv`, [2](#), [14](#), [15](#)