

Package ‘ssrn’

May 9, 2026

Title Scan Statistics for Railway Network

Version 0.1.0

Date 2020-06-14

Description Implement the algorithm provided in scan for estimating the transmission route on railway network using passenger volume. It is a generalization of the scan statistic approach for railway network to identify the hot railway route for transmitting infectious diseases.

URL <https://github.com/uribo/ssrn>

BugReports <https://github.com/uribo/ssrn/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Depends R (>= 3.2.0)

Imports dplyr (>= 1.0.0), magrittr (>= 1.5), purrr (>= 0.3.4), rlang (>= 0.4.6), stringr (>= 1.4.0), tibble (>= 3.0.1), tidyr (>= 1.1.0)

Suggests testthat, scanstatistics

NeedsCompilation no

Author Shinya Uryu [aut, cre] (ORCID: <<https://orcid.org/0000-0002-0493-6186>>),
Yuta Tanoue [aut],
Daisuke Yoneoka [aut]

Maintainer Shinya Uryu <suika1127@gmail.com>

Repository CRAN

Date/Publication 2020-06-23 13:40:03 UTC

Contents

jreast_jt	2
jreast_jt_od	2
make_adjacency_matrix	3
make_passenger_matrix	3
make_passenger_od	4
network_window	5
transit_table	5

Index	7
--------------	----------

jreast_jt	<i>East Japan Railway's Tokaido Line Data</i>
-----------	---

Description

East Japan Railway's Tokaido Line Data

Details

Includes the names of stations between Tokyo and Yugawara as of June 2020.

- st_code: A unique number to identify the station.
- st_name: Romanization of station names.

Value

- jreast_jt a tibble

jreast_jt_od	<i>JR-East Tokaido Line OD Data</i>
--------------	-------------------------------------

Description

JR-East Tokaido Line OD Data

Details

Census values made in 2015. The number of passengers between stations on the Tokaido Line. These values are those of commuter pass users.

- departure_st_code: Departing station identification number.
- arrive_st_code: The identification number of the station you are arriving at.
- volume Number of people getting on and off the train.

Value

- jreast_jt_od a tibble

See Also

https://www.mlit.go.jp/sogoseisaku/transport/sosei_transport_tk_000035.html

make_adjacency_matrix *Convert station data to adjacency matrix*

Description

Convert station data to adjacency matrix

Usage

```
make_adjacency_matrix(stations, depart, arrive)
```

Arguments

stations	data.frame which set of stopping points recorded in order of stopping.
depart	Column name of a stop.
arrive	Give the name of the column indicating the next stop at the target stop.

Examples

```
make_adjacency_matrix(jreast_jt, st_code, next_st_code)
```

make_passenger_matrix *Convert passenger and station data to origin-destination matrix*

Description

Convert passenger and station data to origin-destination matrix

Usage

```
make_passenger_matrix(passenger, stations, depart, arrive, location, value)
```

Arguments

passenger	passenger data
stations	data.frame which set of stopping points recorded in order of stopping.
depart	Column name of a stop.
arrive	Give the name of the column indicating the next stop at the target stop.
location	Name of the variable to use for the join, indicating its location.
value	origin-destination value name

Examples

```
jreast_jt_od %>%
  make_passenger_matrix(jreast_jt,
                        departure_st_code,
                        arrive_st_code,
                        st_code,
                        volume)
```

make_passenger_od *Summaries a passenger volume*

Description

Summaries a passenger volume

Usage

```
make_passenger_od(
  passenger,
  stations,
  depart,
  arrive,
  location,
  value,
  .all = FALSE
)
```

Arguments

passenger	passenger data
stations	data.frame which set of stopping points recorded in order of stopping.
depart	Column name of a stop.
arrive	Give the name of the column indicating the next stop at the target stop.
location	Name of the variable to use for the join, indicating its location.
value	origin-destination value name
.all	Make a join that contains rows of two datasets. The default value is <i>FALSE</i> .

Examples

```
jreast_jt_od %>%
  make_passenger_od(jreast_jt,
                    depart = departure_st_code,
                    arrive_st_code,
                    location = st_code,
                    value = volume) %>%
  dplyr::left_join(jreast_jt %>%
```

```
dplyr::select(arrive_st_code = st_code,
              next_st_name = st_name),
by = "arrive_st_code")
```

network_window	<i>Create network window zones</i>
----------------	------------------------------------

Description

Create network window zones

Usage

```
network_window(adjacency_matrix, dist_matrix, type, cluster_max)
```

Arguments

adjacency_matrix	A boolean matrix, with element (i,j) set to TRUE if location j is adjacent to location i .
dist_matrix	Distance matrix
type	Currently, "connected_B" only.
cluster_max	Maximum cluster size. Zone If this value is reached, the area will not be expanded any further. It's a good idea to keep it to the number of stops on the line you're dealing with.

transit_table	<i>Create transit table</i>
---------------	-----------------------------

Description

Create transit table

Usage

```
transit_table(stations, ..., reverse = FALSE)
```

Arguments

stations	data.frame which set of stopping points recorded in order of stopping.
...	Arguments passed on to <code>dplyr::across</code>
	<code>.cols <tidy-select></code> Columns to transform. Because <code>across()</code> is used within functions like <code>summarise()</code> and <code>mutate()</code> , you can't select or compute upon grouping variables.
reverse	Option to swap the order of the stopping points.

Examples

```
# The next stop is stored in the variable of column next_.
jreast_jt %>%
  transit_table()
# Switch between inbound and outbound lines.
jreast_jt %>%
  transit_table(reverse = TRUE)
```

Index

`dplyr::across`, 5

`jreast_jt`, 2

`jreast_jt_od`, 2

`make_adjacency_matrix`, 3

`make_passenger_matrix`, 3

`make_passenger_od`, 4

`network_window`, 5

`transit_table`, 5