

Package ‘tidyAML’

January 9, 2024

Title Automatic Machine Learning with 'tidymodels'

Version 0.0.4

Description The goal of this package will be to provide a simple interface for automatic machine learning that fits the 'tidymodels' framework. The intention is to work for regression and classification problems with a simple verb framework.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.3

URL <https://github.com/spsanderson/tidyAML>

BugReports <https://github.com/spsanderson/tidyAML/issues>

Depends parsnip, R (>= 4.1.0)

Suggests knitr, rmarkdown, roxygen2, stats, tibble, stringr, utils, recipes, multilevelmod, rules, poissonreg, censored, baguette, bonsai, brulee, rstanarm, dbarts, kknn, ranger, randomForest, LiblineaR, flexsurv, gee, glmnet, discrim, kernlab, klaR, mda, sda, sparsediscrim

VignetteBuilder knitr

Imports rlang (>= 0.4.11), purrr (>= 0.3.5), dplyr (>= 1.0.10), rsample (>= 1.1.0), workflows (>= 1.1.2), forcats, workflowsets, tidyr, broom

NeedsCompilation no

Author Steven Sanderson [aut, cre, cph]
(<<https://orcid.org/0009-0006-7661-8247>>)

Maintainer Steven Sanderson <spsanderson@gmail.com>

Repository CRAN

Date/Publication 2024-01-09 20:00:02 UTC

R topics documented:

core_packages	2
create_model_spec	3
create_splits	4
create_workflow_set	5
extract_model_spec	6
extract_regression_residuals	7
extract_wflw	8
extract_wflw_fit	9
extract_wflw_pred	10
fast_classification	11
fast_classification_parsnip_spec_tbl	13
fast_regression	14
fast_regression_parsnip_spec_tbl	15
full_internal_make_wflw	16
get_model	18
install_deps	19
internal_make_fitted_wflw	19
internal_make_spec_tbl	21
internal_make_wflw	22
internal_make_wflw_gee_lin_reg	23
internal_make_wflw_predictions	24
internal_set_args_to_tune	25
load_deps	26
make_classification_base_tbl	27
make_regression_base_tbl	28
match_args	28
Index	30

core_packages	<i>Functions to Install all Core Libraries</i>
---------------	--

Description

Lists the core packages necessary to run all potential modeling algorithms.

Usage

```
core_packages()
```

Details

Lists the core packages necessary to run all potential modeling algorithms.

Value

A character vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [create_splits\(\)](#), [create_workflow_set\(\)](#), [fast_classification_parsnip_spec_tbl\(\)](#), [fast_regression_parsnip_spec_tbl\(\)](#), [full_internal_make_wflw\(\)](#), [install_deps\(\)](#), [load_deps\(\)](#), [match_args\(\)](#)

Examples

```
core_packages()
```

create_model_spec	<i>Generate Model Specification calls to parsnip</i>
-------------------	--

Description

Creates a list/tibble of parsnip model specifications.

Usage

```
create_model_spec(  
  .parsnip_eng = list("lm"),  
  .mode = list("regression"),  
  .parsnip_fns = list("linear_reg"),  
  .return_tibble = TRUE  
)
```

Arguments

<code>.parsnip_eng</code>	The input must be a list. The default for this is set to <code>all</code> . This means that all of the parsnip linear regression engines will be used, for example <code>lm</code> , or <code>glm</code> .
<code>.mode</code>	The input must be a list. The default is <code>'regression'</code>
<code>.parsnip_fns</code>	The input must be a list. The default for this is set to <code>all</code> . This means that all of the parsnip linear regression functions will be used, for example <code>linear_reg()</code> , or <code>cubist_rules</code> .
<code>.return_tibble</code>	The default is <code>TRUE</code> . <code>FALSE</code> will return a list object.

Details

Creates a list/tibble of parsnip model specifications. With this function you can generate a list/tibble output of any model specification and engine you choose that is supported by the parsnip ecosystem.

Value

A list or a tibble.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Model_Generator: [fast_classification\(\)](#), [fast_regression\(\)](#)

Examples

```
create_model_spec(
  .parsnip_eng = list("lm", "glm", "glmnet", "cubist"),
  .parsnip_fns = list(
    "linear_reg", "linear_reg", "linear_reg",
    "cubist_rules"
  )
)

create_model_spec(
  .parsnip_eng = list("lm", "glm", "glmnet", "cubist"),
  .parsnip_fns = list(
    "linear_reg", "linear_reg", "linear_reg",
    "cubist_rules"
  ),
  .return_tibble = FALSE
)
```

create_splits

Utility Create Splits Object

Description

Create a splits object.

Usage

```
create_splits(.data, .split_type = "initial_split", .split_args = NULL)
```

Arguments

.data	The data being passed to make a split on
.split_type	The default is "initial_split", you can pass any other split type from the <code>rsample</code> library.
.split_args	The default is <code>NULL</code> in order to use the default split arguments. If you want to pass other arguments then must pass a list with the parameter name and the argument.

Details

Create a splits object that returns a list object of both the splits object itself and the splits type. This function supports all splits types from the `rsample` package.

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [core_packages\(\)](#), [create_workflow_set\(\)](#), [fast_classification_parsnip_spec_tbl\(\)](#), [fast_regression_parsnip_spec_tbl\(\)](#), [full_internal_make_wflw\(\)](#), [install_deps\(\)](#), [load_deps\(\)](#), [match_args\(\)](#)

Examples

```
create_splits(mtcars, .split_type = "vfold_cv")
```

create_workflow_set *Create a Workflow Set Object*

Description

Create a workflow set object tibble from a model spec tibble.

Usage

```
create_workflow_set(.model_tbl = NULL, .recipe_list = list(), .cross = TRUE)
```

Arguments

- | | |
|---------------------------|--|
| <code>.model_tbl</code> | The model table that is generated from a function like <code>fast_regression_parsnip_spec_tbl()</code> . The model spec column will be grabbed automatically as the class of the object must be <code>tidyml_base_tbl</code> |
| <code>.recipe_list</code> | Provide a list of recipes here that will get added to the workflow set object. |
| <code>.cross</code> | The default is <code>TRUE</code> , can be set to <code>FALSE</code> . This is passed to the <code>cross</code> parameter as an argument to the <code>workflow_set()</code> function. |

Details

Create a workflow set object/tibble from a model spec tibble where the object class type is `tidyml_base_tbl`. This function will take in a list of recipes and will grab the model specifications from the base tibble to create the workflow sets object. You can also supply the logical of TRUE/FALSE the `.cross` parameter which gets passed to the corresponding parameter as an argument to the `workflowsets::workflow_set()` function.

Value

A list object of workflows.

Author(s)

Steven P. Sanderson II, MPH

See Also

<https://workflowsets.tidymodels.org/>

Other Utility: `core_packages()`, `create_splits()`, `fast_classification_parsnip_spec_tbl()`, `fast_regression_parsnip_spec_tbl()`, `full_internal_make_wflw()`, `install_deps()`, `load_deps()`, `match_args()`

Examples

```
library(recipes)

rec_obj <- recipe(mpg ~ ., data = mtcars)
spec_tbl <- fast_regression_parsnip_spec_tbl(
  .parsnip_fns = "linear_reg",
  .parsnip_eng = c("lm", "glm")
)

create_workflow_set(
  spec_tbl,
  list(rec_obj)
)
```

extract_model_spec *Extract A Model Specification*

Description

Extract a model specification from a tidyAML model tibble.

Usage

```
extract_model_spec(.data, .model_id = NULL)
```

Arguments

`.data` The model table that must have the class `tidyml_mod_spec_tbl`.
`.model_id` The model number that you want to select, Must be an integer or sequence of integers, ie. 1 or `c(1,3,5)` or `1:2`

Details

This function allows you to get a model specification or more from a tibble with a class of `"tidyml_mod_spec_tbl"`. It allows you to select the model by the `.model_id` column. You can call the model id's by an integer or a sequence of integers.

Value

A tibble with the chosen model specification(s).

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Extractor: [extract_regression_residuals\(\)](#), [extract_wflw_fit\(\)](#), [extract_wflw_pred\(\)](#), [extract_wflw\(\)](#), [get_model\(\)](#)

Examples

```
spec_tbl <- fast_regression_parsnip_spec_tbl(  
  .parsnip_fns = "linear_reg",  
  .parsnip_eng = c("lm", "glm")  
)  
  
extract_model_spec(spec_tbl, 1)  
extract_model_spec(spec_tbl, 1:2)
```

extract_regression_residuals

Extract Residuals from Fast Regression Models

Description

This function extracts residuals from a fast regression model table (`fast_regression()`).

Usage

```
extract_regression_residuals(.model_tbl, .pivot_long = FALSE)
```

Arguments

- `.model_tbl` A fast regression model specification table (`fst_reg_spec_tbl`).
- `.pivot_long` A logical value indicating if the output should be pivoted. The default is `FALSE`.

Details

The function checks if the input model specification table inherits the class `'fst_reg_spec_tbl'` and if it contains the column `'pred_wflw'`. It then manipulates the data, grouping it by model, and extracts residuals for each model. The result is a list of data frames, each containing residuals, actual values, and predicted values for a specific model.

Value

The function returns a list of data frames, each containing residuals, actual values, and predicted values for a specific model.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Extractor: [extract_model_spec\(\)](#), [extract_wflw_fit\(\)](#), [extract_wflw_pred\(\)](#), [extract_wflw\(\)](#), [get_model\(\)](#)

Examples

```
library(recipes, quietly = TRUE)

rec_obj <- recipe(mpg ~ ., data = mtcars)

fr_tbl <- fast_regression(mtcars, rec_obj, .parsnip_eng = c("lm", "glm"),
  .parsnip_fns = "linear_reg")

extract_regression_residuals(fr_tbl)
extract_regression_residuals(fr_tbl, .pivot_long = TRUE)
```

extract_wflw

Extract A Model Workflow

Description

Extract a model workflow from a tidyAML model tibble.

Usage

```
extract_wflw(.data, .model_id = NULL)
```


Arguments

<code>.data</code>	The model table that must have the class <code>tidyml_mod_spec_tbl</code> .
<code>.model_id</code>	The model number that you want to select, Must be an integer or sequence of integers, ie. 1 or <code>c(1,3,5)</code> or <code>1:2</code>

Details

This function allows you to get a model workflow or more from a tibble with a class of `"tidyml_mod_spec_tbl"`. It allows you to select the model by the `.model_id` column. You can call the model id's by an integer or a sequence of integers.

Value

A tibble with the chosen model workflow(s).

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Extractor: [extract_model_spec\(\)](#), [extract_regression_residuals\(\)](#), [extract_wflw_fit\(\)](#), [extract_wflw_pred\(\)](#), [get_model\(\)](#)

Examples

```
library(recipes)

rec_obj <- recipe(mpg ~ ., data = mtcars)
frit_tbl <- fast_regression(mtcars, rec_obj, .parsnip_eng = c("lm", "glm"),
                          .parsnip_fns = "linear_reg")

extract_wflw(frit_tbl, 1)
extract_wflw(frit_tbl, 1:2)
```

`extract_wflw_fit` *Extract A Model Fitted Workflow*

Description

Extract a model fitted workflow from a tidyAML model tibble.

Usage

```
extract_wflw_fit(.data, .model_id = NULL)
```

Arguments

`.data` The model table that must have the class `tidyml_mod_spec_tbl`.
`.model_id` The model number that you want to select, Must be an integer or sequence of integers, ie. 1 or `c(1,3,5)` or `1:2`

Details

This function allows you to get a model fitted workflow or more from a tibble with a class of `"tidyml_mod_spec_tbl"`. It allows you to select the model by the `.model_id` column. You can call the model id's by an integer or a sequence of integers.

Value

A tibble with the chosen model workflow(s).

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Extractor: [extract_model_spec\(\)](#), [extract_regression_residuals\(\)](#), [extract_wflw_pred\(\)](#), [extract_wflw\(\)](#), [get_model\(\)](#)

Examples

```
library(recipes)

rec_obj <- recipe(mpg ~ ., data = mtcars)
frit_tbl <- fast_regression(mtcars, rec_obj, .parsnip_eng = c("lm","glm"),
                          .parsnip_fns = "linear_reg")

extract_wflw_fit(frit_tbl, 1)
extract_wflw_fit(frit_tbl, 1:2)
```

`extract_wflw_pred` *Extract A Model Workflow Predictions*

Description

Extract a model workflow predictions from a tidyAML model tibble.

Usage

```
extract_wflw_pred(.data, .model_id = NULL)
```

Arguments

<code>.data</code>	The model table that must have the class <code>tidyml_mod_spec_tbl</code> .
<code>.model_id</code>	The model number that you want to select, Must be an integer or sequence of integers, ie. 1 or <code>c(1, 3, 5)</code> or <code>1:2</code>

Details

This function allows you to get a model workflow predictions or more from a tibble with a class of "tidyml_mod_spec_tbl". It allows you to select the model by the `.model_id` column. You can call the model id's by an integer or a sequence of integers.

Value

A tibble with the chosen model workflow(s).

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Extractor: [extract_model_spec\(\)](#), [extract_regression_residuals\(\)](#), [extract_wflw_fit\(\)](#), [extract_wflw\(\)](#), [get_model\(\)](#)

Examples

```
library(recipes)

rec_obj <- recipe(mpg ~ ., data = mtcars)
frt_tbl <- fast_regression(mtcars, rec_obj, .parsnip_eng = c("lm", "glm"),
                          .parsnip_fns = "linear_reg")

extract_wflw_pred(frt_tbl, 1)
extract_wflw_pred(frt_tbl, 1:2)
```

`fast_classification` *Generate Model Specification calls to parsnip*

Description

Creates a list/tibble of parsnip model specifications.

Usage

```
fast_classification(  
  .data,  
  .rec_obj,  
  .parsnip_fns = "all",  
  .parsnip_eng = "all",  
  .split_type = "initial_split",  
  .split_args = NULL,  
  .drop_na = TRUE  
)
```

Arguments

<code>.data</code>	The data being passed to the function for the classification problem
<code>.rec_obj</code>	The recipe object being passed.
<code>.parsnip_fns</code>	The default is 'all' which will create all possible classification model specifications supported.
<code>.parsnip_eng</code>	the default is 'all' which will create all possible classification model specifications supported.
<code>.split_type</code>	The default is 'initial_split', you can pass any type of split supported by <code>rsample</code>
<code>.split_args</code>	The default is NULL, when NULL then the default parameters of the split type will be executed for the <code>rsample</code> split type.
<code>.drop_na</code>	The default is TRUE, which will drop all NA's from the data.

Details

With this function you can generate a tibble output of any classification model specification and it's fitted workflow object. Per recipes documentation explicitly with `step_string2factor()` it is encouraged to mutate your predictor into a factor before you create your recipe.

Value

A list or a tibble.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Model_Generator: [create_model_spec\(\)](#), [fast_regression\(\)](#)

Examples

```
library(recipes)  
library(dplyr)  
library(tidyr)
```

```
df <- Titanic |>
  as_tibble() |>
  uncount(n) |>
  mutate(across(everything(), as.factor))

rec_obj <- recipe(Survived ~ ., data = df)

fct_tbl <- fast_classification(
  .data = df,
  .rec_obj = rec_obj,
  .parsnip_eng = c("glm", "earth")
)

fct_tbl
```

fast_classification_parsnip_spec_tbl

Utility Classification call to parsnip

Description

Creates a tibble of parsnip classification model specifications.

Usage

```
fast_classification_parsnip_spec_tbl(
  .parsnip_fns = "all",
  .parsnip_eng = "all"
)
```

Arguments

`.parsnip_fns` The default for this is set to `all`. This means that all of the parsnip **classification** functions will be used, for example `bag_mars()`, or `bart()`. You can also choose to pass a `c()` vector like `c("barg_mars", "bart")`

`.parsnip_eng` The default for this is set to `all`. This means that all of the parsnip **classification engines** will be used, for example `earth`, or `dbarts`. You can also choose to pass a `c()` vector like `c('earth', 'dbarts')`

Details

Creates a tibble of parsnip classification model specifications. This will create a tibble of 32 different classification model specifications which can be filtered. The model specs are created first and then filtered out. This will only create models for **classification** problems. To find all of the supported models in this package you can visit <https://www.tidymodels.org/find/parsnip/>

Value

A tibble with an added class of 'fst_class_spec_tbl'

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [core_packages\(\)](#), [create_splits\(\)](#), [create_workflow_set\(\)](#), [fast_regression_parsnip_spec_tbl\(\)](#), [full_internal_make_wflw\(\)](#), [install_deps\(\)](#), [load_deps\(\)](#), [match_args\(\)](#)

Examples

```
fast_classification_parsnip_spec_tbl(.parsnip_fns = "logistic_reg")
fast_classification_parsnip_spec_tbl(.parsnip_eng = c("earth", "dbarts"))
```

fast_regression	<i>Generate Model Specification calls to parsnip</i>
-----------------	--

Description

Creates a list/tibble of parsnip model specifications.

Usage

```
fast_regression(
  .data,
  .rec_obj,
  .parsnip_fns = "all",
  .parsnip_eng = "all",
  .split_type = "initial_split",
  .split_args = NULL,
  .drop_na = TRUE
)
```

Arguments

.data	The data being passed to the function for the regression problem
.rec_obj	The recipe object being passed.
.parsnip_fns	The default is 'all' which will create all possible regression model specifications supported.
.parsnip_eng	the default is 'all' which will create all possible regression model specifications supported.
.split_type	The default is 'initial_split', you can pass any type of split supported by <code>rsample</code>

- `.split_args` The default is NULL, when NULL then the default parameters of the split type will be executed for the rsample split type.
- `.drop_na` The default is TRUE, which will drop all NA's from the data.

Details

With this function you can generate a tibble output of any regression model specification and it's fitted workflow object.

Value

A list or a tibble.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Model_Generator: [create_model_spec\(\)](#), [fast_classification\(\)](#)

Examples

```
library(recipes, quietly = TRUE)

rec_obj <- recipe(mpg ~ ., data = mtcars)
frr_tbl <- fast_regression(
  mtcars,
  rec_obj,
  .parsnip_eng = c("lm", "glm", "gee"),
  .parsnip_fns = "linear_reg"
)

frr_tbl
```

fast_regression_parsnip_spec_tbl

Utility Regression call to parsnip

Description

Creates a tibble of parsnip regression model specifications.

Usage

```
fast_regression_parsnip_spec_tbl(.parsnip_fns = "all", .parsnip_eng = "all")
```

Arguments

- `.parsnip_fns` The default for this is set to `all`. This means that all of the parsnip **linear regression** functions will be used, for example `linear_reg()`, or `cubist_rules`. You can also choose to pass a `c()` vector like `c("linear_reg", "cubist_rules")`
- `.parsnip_eng` The default for this is set to `all`. This means that all of the parsnip **linear regression engines** will be used, for example `lm`, or `glm`. You can also choose to pass a `c()` vector like `c('lm', 'glm')`

Details

Creates a tibble of parsnip regression model specifications. This will create a tibble of 46 different regression model specifications which can be filtered. The model specs are created first and then filtered out. This will only create models for **regression** problems. To find all of the supported models in this package you can visit <https://www.tidymodels.org/find/parsnip/>

Value

A tibble with an added class of `'fst_reg_spec_tbl'`

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [core_packages\(\)](#), [create_splits\(\)](#), [create_workflow_set\(\)](#), [fast_classification_parsnip_spec_tbl\(\)](#), [full_internal_make_wflw\(\)](#), [install_deps\(\)](#), [load_deps\(\)](#), [match_args\(\)](#)

Examples

```
fast_regression_parsnip_spec_tbl(.parsnip_fns = "linear_reg")
fast_regression_parsnip_spec_tbl(.parsnip_eng = c("lm", "glm"))
```

full_internal_make_wflw

Full Internal Workflow for Model and Recipe

Description

This function creates a full internal workflow for a model and recipe combination.

Usage

```
full_internal_make_wflw(.model_tbl, .rec_obj)
```


Arguments

.model_tbl A model specification table (tidyml_mod_spec_tbl).
.rec_obj A recipe object.

Details

The function checks if the input model specification table inherits the class 'tidyml_mod_spec_tbl'. It then manipulates the input table, making adjustments for factors and creating a list of grouped models. For each model-recipe pair, it uses the appropriate internal function based on the model type to create a workflow object. The specific internal function is selected using a switch statement based on the class of the model.

Value

The function returns a workflow object for the first model-recipe pair based on the internal function selected.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [core_packages\(\)](#), [create_splits\(\)](#), [create_workflow_set\(\)](#), [fast_classification_parsnip_spec_tbl\(\)](#), [fast_regression_parsnip_spec_tbl\(\)](#), [install_deps\(\)](#), [load_deps\(\)](#), [match_args\(\)](#)

Examples

```
library(dplyr)
library(recipes)

rec_obj <- recipe(mpg ~ ., data = mtcars)

mod_tbl <- make_regression_base_tbl()
mod_tbl <- mod_tbl |>
  filter(
    .parsnip_engine %in% c("lm", "glm") &
    .parsnip_fns == "linear_reg"
  )
class(mod_tbl) <- c("tidyml_mod_spec_tbl", class(mod_tbl))
mod_spec_tbl <- internal_make_spec_tbl(mod_tbl)
result <- full_internal_make_wflw(mod_spec_tbl, rec_obj)
result
```

get_model	<i>Get a Model</i>
-----------	--------------------

Description

Get a model from a tidyAML model tibble.

Usage

```
get_model(.data, .model_id = NULL)
```

Arguments

.data	The model table that must have the class <code>tidyaml_mod_spec_tbl</code> .
.model_id	The model number that you want to select, Must be an integer or sequence of integers, ie. 1 or <code>c(1,3,5)</code> or <code>1:2</code>

Details

This function allows you to get a model or models from a tibble with a class of `"tidyaml_mod_spec_tbl"`. It allows you to select the model by the `.model_id` column. You can call the model id's by an integer or a sequence of integers.

Value

A tibble with the chosen models.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Extractor: [extract_model_spec\(\)](#), [extract_regression_residuals\(\)](#), [extract_wflw_fit\(\)](#), [extract_wflw_pred\(\)](#), [extract_wflw\(\)](#)

Examples

```
library(recipes)

rec_obj <- recipe(mpg ~ ., data = mtcars)
spec_tbl <- fast_regression_parsnip_spec_tbl(
  .parsnip_fns = "linear_reg",
  .parsnip_eng = c("lm", "glm")
)

get_model(spec_tbl, 1)
get_model(spec_tbl, 1:2)
```

`install_deps`*Functions to Install all Core Libraries*

Description

Installs all dependencies in the `core_packages()` function.

Usage

```
install_deps()
```

Details

Installs all dependencies in the `core_packages()` function.

Value

No return value, called for side effects

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [core_packages\(\)](#), [create_splits\(\)](#), [create_workflow_set\(\)](#), [fast_classification_parsnip_spec_tbl\(\)](#), [fast_regression_parsnip_spec_tbl\(\)](#), [full_internal_make_wflw\(\)](#), [load_deps\(\)](#), [match_args\(\)](#)

Examples

```
## Not run:  
  install_deps()  
  
## End(Not run)
```

`internal_make_fitted_wflw`*Internals Safely Make a Fitted Workflow from Model Spec tibble*

Description

Safely Make a fitted workflow from a model spec tibble.

Usage

```
internal_make_fitted_wflw(.model_tbl, .splits_obj)
```

Arguments

- `.model_tbl` The model table that is generated from a function like `fast_regression_parsnip_spec_tbl()`, must have a class of `"tidyml_mod_spec_tbl"`. This is meant to be used after the function `internal_make_wflw()` has been run and the tibble has been saved.
- `.splits_obj` The splits object from the `auto_ml` function. It is internal to the `auto_ml` function.

Details

Create a fitted parsnip model from a workflow object.

Value

A list object of workflows.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: [internal_make_spec_tbl\(\)](#), [internal_make_wflw_gee_lin_reg\(\)](#), [internal_make_wflw_prediction\(\)](#), [internal_make_wflw\(\)](#), [internal_set_args_to_tune\(\)](#), [make_classification_base_tbl\(\)](#), [make_regression_base_tbl\(\)](#)

Examples

```
library(recipes, quietly = TRUE)

mod_spec_tbl <- fast_regression_parsnip_spec_tbl(
  .parsnip_eng = c("lm", "glm"),
  .parsnip_fns = "linear_reg"
)

rec_obj <- recipe(mpg ~ ., data = mtcars)
splits_obj <- create_splits(mtcars, "initial_split")

mod_tbl <- mod_spec_tbl |>
  mutate(wflw = full_internal_make_wflw(mod_spec_tbl, rec_obj))

internal_make_fitted_wflw(mod_tbl, splits_obj)
```

`internal_make_spec_tbl`*Internals Make a Model Spec tibble*

Description

Make a Model Spec tibble.

Usage

```
internal_make_spec_tbl(.model_tbl)
```

Arguments

`.model_tbl` This is the data that should be coming from inside of the regression/classification to parsnip spec functions.

Details

Make a Model Spec tibble.

Value

A model spec tbl.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: [internal_make_fitted_wflw\(\)](#), [internal_make_wflw_gee_lin_reg\(\)](#), [internal_make_wflw_predict\(\)](#), [internal_make_wflw\(\)](#), [internal_set_args_to_tune\(\)](#), [make_classification_base_tbl\(\)](#), [make_regression_base_tbl\(\)](#)

Examples

```
make_regression_base_tbl() |>  
  internal_make_spec_tbl()
```

```
make_classification_base_tbl() |>  
  internal_make_spec_tbl()
```

internal_make_wflw *Internals Safely Make Workflow from Model Spec tibble*

Description

Safely Make a workflow from a model spec tibble.

Usage

```
internal_make_wflw(.model_tbl, .rec_obj)
```

Arguments

`.model_tbl` The model table that is generated from a function like `fast_regression_parsnip_spec_tbl()`, must have a class of "tidyml_mod_spec_tbl".

`.rec_obj` The recipe object that is going to be used to make the workflow object.

Details

Create a model specification tibble that has a `workflows::workflow()` list column.

Value

A list object of workflows.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: [internal_make_fitted_wflw\(\)](#), [internal_make_spec_tbl\(\)](#), [internal_make_wflw_gee_lin_reg\(\)](#), [internal_make_wflw_predictions\(\)](#), [internal_set_args_to_tune\(\)](#), [make_classification_base_tbl\(\)](#), [make_regression_base_tbl\(\)](#)

Examples

```
library(recipes, quietly = TRUE)

mod_spec_tbl <- fast_regression_parsnip_spec_tbl(
  .parsnip_eng = c("lm", "glm", "gee"),
  .parsnip_fns = "linear_reg"
)

rec_obj <- recipe(mpg ~ ., data = mtcars)

internal_make_wflw(mod_spec_tbl, rec_obj)
```

`internal_make_wflw_gee_lin_reg`*Internals Safely Make Workflow for GEE Linear Regression*

Description

Safely Make a workflow from a model spec tibble.

Usage

```
internal_make_wflw_gee_lin_reg(.model_tbl, .rec_obj)
```

Arguments

`.model_tbl` The model table that is generated from a function like `fast_regression_parsnip_spec_tbl()`, must have a class of "tidyml_mod_spec_tbl".

`.rec_obj` The recipe object that is going to be used to make the workflow object.

Details

Create a model specification tibble that has a `workflows::workflow()` list column.

Value

A list object of workflows.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: [internal_make_fitted_wflw\(\)](#), [internal_make_spec_tbl\(\)](#), [internal_make_wflw_predictions\(\)](#), [internal_make_wflw\(\)](#), [internal_set_args_to_tune\(\)](#), [make_classification_base_tbl\(\)](#), [make_regression_base_tbl\(\)](#)

Examples

```
library(dplyr)
library(recipes)
library(multilevelmod)

mod_tbl <- make_regression_base_tbl()
mod_tbl <- mod_tbl |>
  filter(
    .parsnip_engine %in% c("gee") &
    .parsnip_fns == "linear_reg"
  )
```

```

class(mod_tbl) <- c("tidyml_mod_spec_tbl", class(mod_tbl))
mod_spec_tbl <- internal_make_spec_tbl(mod_tbl)
rec_obj <- recipe(mpg ~ ., data = mtcars)

internal_make_wflw_gee_lin_reg(mod_spec_tbl, rec_obj)

```

internal_make_wflw_predictions

Internals Safely Make Predictions on a Fitted Workflow from Model Spec tibble

Description

Safely Make predictions on a fitted workflow from a model spec tibble.

Usage

```
internal_make_wflw_predictions(.model_tbl, .splits_obj)
```

Arguments

`.model_tbl` The model table that is generated from a function like `fast_regression_parsnip_spec_tbl()`, must have a class of "tidyml_mod_spec_tbl". This is meant to be used after the function `internal_make_fitted_wflw()` has been run and the tibble has been saved.

`.splits_obj` The splits object from the `auto_ml` function. It is internal to the `auto_ml` function.

Details

Create predictions on a fitted parsnip model from a workflow object.

Value

A list object tibble of the outcome variable and its values along with the testing and training predictions in a single tibble.

.data_category	.data_type	.value
actual	actual	21.0
actual	actual	21.0
actual	actual	22.8
...
predicted	training	21.0
...
predicted	training	21.0

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: [internal_make_fitted_wflw\(\)](#), [internal_make_spec_tbl\(\)](#), [internal_make_wflw_gee_lin_reg\(\)](#), [internal_make_wflw\(\)](#), [internal_set_args_to_tune\(\)](#), [make_classification_base_tbl\(\)](#), [make_regression_base_tbl\(\)](#)

Examples

```
library(recipes, quietly = TRUE)

mod_spec_tbl <- fast_regression_parsnip_spec_tbl(
  .parsnip_eng = c("lm", "glm"),
  .parsnip_fns = "linear_reg"
)

rec_obj <- recipe(mpg ~ ., data = mtcars)
splits_obj <- create_splits(mtcars, "initial_split")

mod_tbl <- mod_spec_tbl |>
  mutate(wflw = full_internal_make_wflw(mod_spec_tbl, rec_obj))

mod_fitted_tbl <- mod_tbl |>
  mutate(fitted_wflw = internal_make_fitted_wflw(mod_tbl, splits_obj))

internal_make_wflw_predictions(mod_fitted_tbl, splits_obj)
```

internal_set_args_to_tune

Internals Make a Tunable Model Specification

Description

Make a tuned model specification object.

Usage

```
internal_set_args_to_tune(.model_tbl)
```

Arguments

`.model_tbl` The model table that is generated from a function like `fast_regression_parsnip_spec_tbl()`, must have a class of `"tidyml_mod_spec_tbl"`.

Details

This will take a model specification that is created from a function like `fast_regression_parsnip_spec_tbl()` and update the **model_spec** args to `tune::tune()`. This is done dynamically, meaning you do not need to know the names of the parameters inside of the model specification.

Value

A list object of workflows.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: `internal_make_fitted_wflw()`, `internal_make_spec_tbl()`, `internal_make_wflw_gee_lin_reg()`, `internal_make_wflw_predictions()`, `internal_make_wflw()`, `make_classification_base_tbl()`, `make_regression_base_tbl()`

Examples

```
library(dplyr)

mod_tbl <- fast_regression_parsnip_spec_tbl()
mod_tbl$model_spec[[1]]

updated_mod_tbl <- mod_tbl |>
  mutate(model_spec = internal_set_args_to_tune(mod_tbl))
updated_mod_tbl$model_spec[[1]]
```

load_deps

Functions to Install all Core Libraries

Description

Load all the core packages necessary to run all potential modeling algorithms.

Usage

```
load_deps()
```

Details

Load all the core packages necessary to run all potential modeling algorithms.

Value

No return value, called for side effects

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [core_packages\(\)](#), [create_splits\(\)](#), [create_workflow_set\(\)](#), [fast_classification_parsnip_spec_tbl\(\)](#), [fast_regression_parsnip_spec_tbl\(\)](#), [full_internal_make_wflow\(\)](#), [install_deps\(\)](#), [match_args\(\)](#)

Examples

```
## Not run:  
load_deps()  
  
## End(Not run)
```

make_classification_base_tbl

Internals Make Base Classification Tibble

Description

Creates a base tibble to create parsnip classification model specifications.

Usage

```
make_classification_base_tbl()
```

Details

Creates a base tibble to create parsnip classification model specifications.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: [internal_make_fitted_wflow\(\)](#), [internal_make_spec_tbl\(\)](#), [internal_make_wflow_gee_lin_reg\(\)](#), [internal_make_wflow_predictions\(\)](#), [internal_make_wflow\(\)](#), [internal_set_args_to_tune\(\)](#), [make_regression_base_tbl\(\)](#)

Examples

```
make_classification_base_tbl()
```

`make_regression_base_tbl`*Internals Make Base Regression Tibble*

Description

Creates a base tibble to create parsnip regression model specifications.

Usage

```
make_regression_base_tbl()
```

Details

Creates a base tibble to create parsnip regression model specifications.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Internals: [internal_make_fitted_wflw\(\)](#), [internal_make_spec_tbl\(\)](#), [internal_make_wflw_gee_lin_reg\(\)](#), [internal_make_wflw_predictions\(\)](#), [internal_make_wflw\(\)](#), [internal_set_args_to_tune\(\)](#), [make_classification_base_tbl\(\)](#)

Examples

```
make_regression_base_tbl()
```

`match_args`*Match function arguments*

Description

Match a functions arguments.

Usage

```
match_args(f, args)
```

Arguments

f	The parsnip function such as "linear_reg" as a string and without the parentheses.
args	The arguments you want to supply to f

Details

Match a functions arguments, the bad ones passed will be rejected but the remaining passing ones will be returned.

Value

A list of matched arguments.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Utility: [core_packages\(\)](#), [create_splits\(\)](#), [create_workflow_set\(\)](#), [fast_classification_parsnip_spec_tbl\(\)](#), [fast_regression_parsnip_spec_tbl\(\)](#), [full_internal_make_wflw\(\)](#), [install_deps\(\)](#), [load_deps\(\)](#)

Examples

```
match_args(  
  f = "linear_reg",  
  args = list(  
    mode = "regression",  
    engine = "lm",  
    trees = 1,  
    mtry = 1  
  )  
)
```

Index

- * **Extractor**
 - extract_model_spec, 6
 - extract_regression_residuals, 7
 - extract_wflw, 8
 - extract_wflw_fit, 9
 - extract_wflw_pred, 10
 - get_model, 18
- * **Internals**
 - internal_make_fitted_wflw, 19
 - internal_make_spec_tbl, 21
 - internal_make_wflw, 22
 - internal_make_wflw_gee_lin_reg, 23
 - internal_make_wflw_predictions, 24
 - internal_set_args_to_tune, 25
 - make_classification_base_tbl, 27
 - make_regression_base_tbl, 28
- * **Model Generator**
 - create_model_spec, 3
 - fast_classification, 11
 - fast_regression, 14
- * **Utility**
 - core_packages, 2
 - create_splits, 4
 - create_workflow_set, 5
 - fast_classification_parsnip_spec_tbl, 13
 - fast_regression_parsnip_spec_tbl, 15
 - full_internal_make_wflw, 16
 - install_deps, 19
 - load_deps, 26
 - match_args, 28
- core_packages, 2, 5, 6, 14, 16, 17, 19, 27, 29
- create_model_spec, 3, 12, 15
- create_splits, 3, 4, 6, 14, 16, 17, 19, 27, 29
- create_workflow_set, 3, 5, 5, 14, 16, 17, 19, 27, 29
- extract_model_spec, 6, 8–11, 18
- extract_regression_residuals, 7, 7, 9–11, 18
- extract_wflw, 7, 8, 8, 10, 11, 18
- extract_wflw_fit, 7–9, 9, 11, 18
- extract_wflw_pred, 7–10, 10, 18
- fast_classification, 4, 11, 15
- fast_classification_parsnip_spec_tbl, 3, 5, 6, 13, 16, 17, 19, 27, 29
- fast_regression, 4, 12, 14
- fast_regression_parsnip_spec_tbl, 3, 5, 6, 14, 15, 17, 19, 27, 29
- fast_regression_parsnip_spec_tbl(), 26
- full_internal_make_wflw, 3, 5, 6, 14, 16, 16, 19, 27, 29
- get_model, 7–11, 18
- install_deps, 3, 5, 6, 14, 16, 17, 19, 27, 29
- internal_make_fitted_wflw, 19, 21–23, 25–28
- internal_make_spec_tbl, 20, 21, 22, 23, 25–28
- internal_make_wflw, 20, 21, 22, 23, 25–28
- internal_make_wflw_gee_lin_reg, 20–22, 23, 25–28
- internal_make_wflw_predictions, 20–23, 24, 26–28
- internal_set_args_to_tune, 20–23, 25, 25, 27, 28
- load_deps, 3, 5, 6, 14, 16, 17, 19, 26, 29
- make_classification_base_tbl, 20–23, 25, 26, 27, 28
- make_regression_base_tbl, 20–23, 25–27, 28
- match_args, 3, 5, 6, 14, 16, 17, 19, 27, 28
- workflows::workflow(), 22, 23
- workflowsets::workflow_set(), 6